



--



Power Toggle Switches

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

No Image Available

147844-1



Active



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Single Pole - Double Throw Configuration (Pole-Throw)
- Toggle Length = 5.33 mm
- Toggle Style = Baton
- Bushing Length = 5.49 mm
- Termination Type = Solder

[View all Features](#) | [Find Similar Products](#)

Documentation & Additional Information

Product Drawings:

- [SUBMINIATURE TOGGLE SWITCH SINGLE POLE](#) (PDF, English)

Catalog Pages/Data Sheets:

- [ALCOSWITCH PRODUCTS](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Configuration (Pole-Throw) = Single Pole - Double Throw
- Termination Type = Solder

Electrical Characteristics:

- Contact Rating = 0.4 VA max @ 20 VDC or peak AC
- Contact Resistance (m?) = 20
- Insulation Resistance (M?) = 1,000

Housing Related Features:

- Toggle Length (mm [in]) = 5.33 [0.210]
- Toggle Style = Baton
- Dielectric Strength (VAC) = 1000

Configuration Related Features:

- Bushing Length (mm [in]) = 5.49 [0.216]

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = Alcoswitch