


B07B332BC1 Product Details



B07B332BC1
(1617003-6)

TE Internal Number: 1617003-6

Active

Military/Aerospace High Performance Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- 07 Full Size Relay Series
- Input Voltage = 26.5 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 10 Amps.
- Non Polarized, Monostable Coil Magnetic System

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • RELAY (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Termination Type = Solder Hook Terminals <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Input Voltage (VDC) = 26.5 • Contact Current Rating (Amps.) = 10 • Coil Polarity Protection Diode = Without • Transistor Driver = Without • Coil Resistance (?) = 300 • MOSFET Driver = Without • Coil Power Measurement = Milliwatts, Volt-Amperes • Coil Power, Nominal (mW) = 2341 • Coil Power, Nominal (VA) = 11.00 • Actuating System = DC • Shock = 50G's, 11ms • Vibration = 20G's, 10 to 2000Hz <p>Body Related Features:</p> <ul style="list-style-type: none"> • Series = 07 Full Size Relay 	<p>Contact Related Features:</p> <ul style="list-style-type: none"> • Mounting Options = Panel Mount • Enclosure = Hermetically Sealed <p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Contact Arrangement = 2 Form C, DPDT, 2 C/O • Coil Magnetic System = Non Polarized, Monostable • Coil Suppression Diode = Without <p>Industry Standards:</p> <ul style="list-style-type: none"> • Government/Industry Qualification = No • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not suitable for lead free processing <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Temperature Range (?C) = -65 - +125 <p>Other:</p> <ul style="list-style-type: none"> • Brand = CII

Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)