

SR-7607 Product Details



SR-7607
(3-1617559-8)

TE Internal Number: 3-1617559-8

 [Active](#)

Military/Aerospace High Performance Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- SR Half-size Relay Series
- Input Voltage = 26.5 VDC
- Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- Contact Current Rating = 2 Amps.
- Non Polarized, Monostable Coil Magnetic System

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
Product Drawings: • None Available Catalog Pages/Data Sheets: • RELAY (PDF, English) Product Specifications: • None Available Application Specifications: • None Available Instruction Sheets: • None Available CAD Files: • None Available	Additional Information: • Product Line Information Related Products: • Tooling
List all Documents	
Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: • Termination Type = PC Pins Electrical Characteristics: • Input Voltage (VDC) = 26.5 • Contact Current Rating (Amps.) = 2 • Coil Polarity Protection Diode = Without • Transistor Driver = Without • Coil Resistance (?) = 390 • MOSFET Driver = Without • Coil Power Measurement = Milliwatts • Coil Power, Nominal (mW) = 1801 • Actuating System = DC • Shock = 100G's, 6ms • Vibration = 15G's, 10 to 2000Hz Body Related Features: • Series = SR Half-size Relay Contact Related Features: • Mounting Options = Chassis Mount • Enclosure = Hermetically Sealed • Approved Standards = M39016 Qualified	Configuration Related Features: • Contact Arrangement = 4 Form C, 4PDT, 4 C/O • Coil Magnetic System = Non Polarized, Monostable • Coil Suppression Diode = Without Industry Standards: • Government/Industry Qualification = Yes • Government/Industry Part Number = M39016/40-007 • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not suitable for lead free processing Conditions for Usage: • Temperature Range (?C) = -65 - +125 Other: • Brand = CII

Corporate Information

[Who We Are](#)

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

Quick Links

[Check Distributor Inventory](#)

[Cross Reference](#)

[Find Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

Customer Support

[Email or Chat with Us](#)

[Find a Phone Number](#)

[Search Knowledge Base](#)

[Manage Your Account](#)