**Ouick Links** 



Search by Keyword or Part #

Check Pricing & Availability Search for Tooling

Product Feature Selector
Contact Us About This Product

**Products** 

**Documentation** 

Resources

**My Account** 

**Customer Support** 

Home > Products > By Type > Relays > Product Feature Selector > Product Details

# 3SBH1138A2 Product Details



3SBH1138A2

(1-1617076-0)




## Military/Aerospace High Performance Relays

Not EU RoHS or ELV Compliant

#### **Product Highlights:**

- 3SBH 1/5-Size Relay Series Input Voltage = 26.5 VDC
- Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- Contact Current Rating = 2 Amps. Non Polarized, Monostable Coil Magnetic System

View all Features









#### **Documentation & Additional Information**

## **Product Drawings:**

### Catalog Pages/Data Sheets:

RELAY (PDF, English)

#### **Product Specifications:**

## **Application Specifications:**

#### **Instruction Sheets:**

None Available

#### **CAD Files:**

None Available

#### **Additional Information:**

**Product Line Information** 

#### **Related Products:**

Tooling

Product Features (Please use the Product Drawing for all design activity)

# **Product Type Features:**

Termination Type = Solder Hook Terminals

## **Electrical Characteristics:**

- Input Voltage (VDC) = 26.5
- Contact Current Rating (Amps.) = 2
- Coil Polarity Protection Diode = Without
- Transistor Driver = Without
- Coil Resistance (?) = 720
- MOSFET Driver = Without
- Coil Power Measurement = Milliwatts
- Coil Power, Nominal (mW) = 975
- Actuating System = DC
- Shock = 75 G's, 6ms
- Vibration = 30G's, 10 to 3000Hz

# **Body Related Features:**

Series = 3SBH 1/5-Size Relay

## **Contact Related Features:**

- Mounting Options = Chassis Mount
- Enclosure = Hermetically Sealed
- Approved Standards = M39016 Qualified, M Level

Configuration Related Features:

- Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- Coil Magnetic System = Non Polarized, Monostable
- Coil Suppression Diode = Without

# **Industry Standards:**

List all Documents

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M39016/14-001M
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Not suitable for lead free processing

## Conditions for Usage:

• Temperature Range (?C) = -65 - +125

## Other:

Brand = CII

**Corporate Information** 

Who We Are

News Room

Investors

**Quick Links** 

Check Distributor Inventory

Cross Reference

Find Documents & Drawings

Supplier Portal **Product Compliance Support Center** Site Map Careers

**Customer Support** 

Email or Chat with Us Find a Phone Number

Search Knowledge Base Manage Your Account

Provide Website Feedback