



<b>Form Type</b>	Distribute	<b>Version</b>	2.0	<b>Ref</b>	IPC 1752A	<b>Sectionals</b>	Manufacturing Info/ Material Info	<b>Subsectionals</b>	D, A
<b>Supplier Information</b>									
<b>Company Name</b>	TE Connectivity	<b>Request Document ID</b>		<b>Contact Name</b>	Chan, Nelson	<b>Contact Title</b>	Manager Sales, HKG SELL DIR-EMS		
<b>Company Unique ID</b>	TE Connectivity	<b>Response Date</b>	2016-09-08	<b>Contact Email</b>	nelson.chan@te.com				
<b>Contact Phone Number</b>	852-2738-8751								
<b>Legal Statement</b>									
<b>Supplier Acceptance</b>	true								
<b>Legal Statement</b>									
The information provided in this document is based upon reasonable inquiry of our suppliers. This information is subject to change. This information does not in any way modify existing purchase specifications or existing contractual or other agreements terms between TE Connectivity (or its affiliated companies) and its customers.									
<b>Product</b>									
<b>Manufacturer Item number</b>	1744057-7	<b>Amount</b>	2000.0	<b>Version</b>	-	<b>Identity</b>			
<b>Manufacturer Item Name</b>	3.96 EP HDR ASSY 7P W/PEGS	<b>Weight Uom</b>	mg	<b>Mfr Site</b>		<b>Authority</b>			
<b>Date</b>		<b>UOM</b>	Each						
<b>EUROHS-0508</b>	Product(s) meets EU RoHS requirement without any exemptions								
<b>ChinaRoHS-0508</b>	Product(s) is eligible for marking with the e code under China's Measures for Administration of the control of pollution by Electronic Information Products								
<b>EUREACH-1215</b>	REACH Candidate Substances of Very High Concern ARE NOT Contained in the Product Above the Limits per the Definition within REACH								
<b>Manufacturing Information</b>									
<b>J-STD-020 MSL Rating</b>		<b>Max Total a Wave Time</b>		<b>Ramp Rate</b>		<b>Wave Additional Info</b>			
<b>Classification Temp</b>		<b>Max Wave Solder Time</b>	10.0	<b>Ramp Down Rate</b>		<b>Psi Rating Reflow</b>			
<b>Max Time Within 5</b>		<b>Psi Rating Wave</b>		<b>Package Designator</b>		<b>Size</b>	0.0		
<b>Time Above 217</b>		<b>Reflow Additional Info</b>		<b>Preheat Max Temp</b>		<b>Terminal Base Alloy</b>	NAC		
<b>Preheat Duration</b>		<b>bulk Solder Termination</b>	NAC	<b>Nbr or Reflow Cycles</b>		<b>Terminal Plating</b>	NAC		
<b>Preheat Min Temp</b>		<b>Nbr of Instances</b>	0	<b>Component Temp Spike</b>		<b>Shape</b>	NAC		
<b>Product Disclosure</b>									
<b>Sub-Item/Material/Substance</b>	<b>Level</b>	<b>Name</b>	<b>Substance Category</b>	<b>Substance CAS</b>	<b>Substance Concentration</b>	<b>Quantity</b>	<b>Mass per Unit</b>	<b>UOM</b>	<b>Exemption</b>
Material	1	Tin - Plating				1.0	15.0	mg	
Substance	2	Copper	Supplier	7440-50-8	0.02	1.0	0.0030	mg	
Substance	2	Tin	Supplier	7440-31-5	99.98	1.0	14.997	mg	
Material	1	HOUSING - NYLON PA66 94V0				1.0	950.0	mg	
Substance	2	Poly[imino(1,6-dioxo-1,6-hexanediyl)imino-1,6-hexanediyl]	Supplier	32131-17-2	92.0	1.0	874.0	mg	
Substance	2	Contains No Reportable TE5081-2 Substances	Supplier	TE5081-2-1212	8.0	1.0	76.0	mg	
Material	1	Nickel Plating				1.0	10.0	mg	
Substance	2	Nickel	Nickel	7440-02-0	100.0	1.0	10.0	mg	
Material	1	Copper PIN - Copper Alloy C2600				1.0	1025.0	mg	
Substance	2	Copper	Supplier	7440-50-8	65.42	1.0	670.555	mg	
Substance	2	Zinc	Supplier	7440-66-6	34.52	1.0	353.83	mg	
Substance	2	Iron	Supplier	7439-89-6	0.03	1.0	0.3075	mg	
Substance	2	Lead	Lead/Lead Compounds	7439-92-1	0.03	1.0	0.3075	mg	