



<b>Form Type</b>	Distribute	<b>Version</b>	2.0	<b>Ref</b>	IPC 1752A	<b>Sectionals</b>	Manufacturing Info/ Material Info	<b>Subsectionals</b>	D, A
<b>Supplier Information</b>									
<b>Company Name</b>	TE Connectivity	<b>Request Document ID</b>		<b>Contact Name</b>	Penica, John R	<b>Contact Title</b>	Sr Mgr Environmental Engineering, IND Central Eng		
<b>Company Unique ID</b>	TE Connectivity	<b>Response Date</b>	2015-12-09	<b>Contact Email</b>	jrpenica@te.com				
<b>Contact Phone Number</b>	+1-717-592-3266								
<b>Legal Statement</b>									
<b>Supplier Acceptance</b>	true								
<b>Legal Statement</b>									
The information provided in this document is based upon reasonable inquiry of our suppliers. This information is subject to change. This information does not in any way modify existing purchase specifications or existing contractual or other agreements terms between TE Connectivity (or its affiliated companies) and its customers.									
<b>Product</b>									
<b>Manufacturer Item number</b>	1-640724-0	<b>Amount</b>	7760.264	<b>Version</b>	-	<b>Identity</b>			
<b>Manufacturer Item Name</b>	15P UMNL STR/REL & INSRT NATL	<b>Weight Uom</b>	mg	<b>Mfr Site</b>		<b>Authority</b>			
<b>Date</b>		<b>UOM</b>	Each						
<b>EUroHS-0508</b>	Product(s) meets EU RoHS requirement without any exemptions								
<b>ChinaRoHS-0508</b>	Product(s) is eligible for marking with the e code under China's Measures for Administration of the control of pollution by Electronic Information Products								
<b>EUREACH-1214</b>	REACH Candidate Substances of Very High Concern ARE NOT Yet Reviewed								
<b>Manufacturing Information</b>									
<b>J-STD-020 MSL Rating</b>		<b>Max Total a Wave Time</b>		<b>Ramp Rate</b>		<b>Wave Additional Info</b>			
<b>Classification Temp</b>		<b>Max Wave Solder Time</b>	0.0	<b>Ramp Down Rate</b>		<b>Psi Rating Reflow</b>			
<b>Max Time Within 5</b>		<b>Psi Rating Wave</b>		<b>Package Designator</b>		<b>Size</b>	0.0		
<b>Time Above 217</b>		<b>Reflow Additional Info</b>		<b>Preheat Max Temp</b>		<b>Terminal Base Alloy</b>	NAC		
<b>Preheat Duration</b>		<b>bulk Solder Termination</b>	NAC	<b>Nbr or Reflow Cycles</b>		<b>Terminal Plating</b>	NAC		
<b>Preheat Min Temp</b>		<b>Nbr of Instances</b>	0	<b>Component Temp Spike</b>		<b>Shape</b>	NAC		
<b>Product Disclosure</b>									
<b>Sub-Item/Material/Substance</b>	<b>Level</b>	<b>Name</b>	<b>Substance Category</b>	<b>Substance CAS</b>	<b>Substance Concentration</b>	<b>Quantity</b>	<b>Mass per Unit</b>	<b>UOM</b>	<b>Exemption</b>
Sub-Item	1	Nylon Compound				1.0	7760.264	mg	
Material	2	PA66				1.0	7760.264	mg	
Substance	3	Poly[imino(1,6-dioxo-1,6-hexanediy)]imino-1,6-hexanediy]	Supplier	32131-17-2	99.355	1.0	7710.2103	mg	
Substance	3	Zinc oxide (ZnO)	Supplier	1314-13-2	0.0020	1.0	0.15521	mg	
Substance	3	Octadecanamide, N,N-1,2-ethanediy]bis-	Supplier	110-30-5	0.3	1.0	23.28079	mg	
Substance	3	Water	Supplier	7732-18-5	0.2	1.0	15.52053	mg	
Substance	3	Aluminum, hydroxybis(octadecanoato-,kappa.O)-	Supplier	300-92-5	0.14	1.0	10.86437	mg	
Substance	3	Siloxanes and Silicones, di-Me	Supplier	63148-62-9	0.0030	1.0	0.23281	mg	