

## HEAT SHRINK TUBING



✓ Active

TE CONNECTIVITY

### RPPM-8/2-X-SP

[Raychem](#) | [RPPM](#)

RPPM-8/2-X-SP

TE Internal Number: 4386414002

Alias ID: 6-1193296-1

[Always EU RoHS/ELV Compliant](#)

Wall Type **Dual**

Resistant To **Abrasion, Fluids**

Low Outgassing **No**

Product Source **Czech Republic**

Packaging Method **Spool**

## Catalog Pages/Data Sheets

[RPPM Pages From 9-1773447-9](#)

PDF  
**English**

## Product Specifications

Product Specification

[RPPM](#)

PDF  
**English**

Please review product documents or [contact us](#) for the latest agency approval information.

### Product Type Features

Wall Type

**Dual**

Product Family

**RPPM**

### Body Features

Shrink Ratio

**4:1**

Color

**Clear**

Flexibility

**Semi-Rigid**

Material

**Irradiated Modified Polyolefin**

Fluid Type

**Typical Automotive Fluids, Water**

### Dimensions

Recovered Inside Diameter (Max)

**2 mm [ .079 in ]**

Recovered Wall Thickness (Tolerance)

**.9 mm [ .0354 in ]**

Expanded Inside Diameter (Min)

**8 mm [ .315 in ]**

Usage Conditions	Resistant To	Abrasion, Fluids
	Recovery Temperature (°C)	80
	Flammability	Non-Flame-Retardant
	Shrink Temperature (Min) (°C)	60
Product Availability	Applicable Region	Asia, EMEA
Packaging Features	Packaging Method	Spool
Other	Low Outgassing	No
	Product Source	Czech Republic
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>		