


HARNESSING

SOLDERSLEEVE SHIELD TERMINATORS



✓ Active

TE CONNECTIVITY

S02-02-W3-22-00-100

[Raychem](#) | [Terminator](#)

CP5533-000

TE Internal Number: CP5533-000

[Always ELV Compliant](#)

[Find Compliant Alternatives](#)

Product Type **Shield Terminator**

Operating Temperature (Max) (°C) **150**

Expanded Inside Diameter (Min) **2.65 mm [.105 in]**

Pre-Installed Lead **No**

Resistance Properties **Immersion Protection**

No documentation available.

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features	Product Type	Shield Terminator
	Temperature Indicator	Yes
	Temperature Indicator Type	Thermochromic
Configuration Features	Pre-Installed Lead	No
Body Features	Shield Outside Diameter (Min)	1.4 mm [.055 in]
Dimensions	Expanded Inside Diameter (Min)	2.65 mm [.105 in]
	Overall Length	16.5 mm [.65 in]
	Jacket Outside Diameter	2.65 mm [.104 in]
Usage Conditions	Operating Temperature (Max) (°C)	150
	Resistance Properties	Immersion Protection
	Wire Temperature (Max) (°C)	125
Industry Standards	Government Qualified	No
	MIL/NAS Specification (MIL-S-83519, NAS-	M83519/1

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)