




MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE) 02 MODII HDR SRST B/A .100CL

AMPMODU | AMPMODU Headers

103321-2

TE Internal Number: 103321-2

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **2**

Header Type **Breakaway**

Product Drawings

[ASSEMBLY, HEADER, BREAKAWAY, MOD II, SINGLE ROW, .100 C/L, VERTICAL, WITH .025 SQUARE POSTS](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Contact Protection	Without
Contact Shape	Square
PCB Mount Retention	Without
Dielectric Withstanding Voltage	750 V
Housing Color	Black
Comment	Headers may be broken to desired number of positions using Hand Tool No. 91406-1, or Tool Kit No. 314818-1. Other tail lengths

are available, consult TE Connectivity.

Packaging Quantity	500
Housing Material	Thermoplastic
Stabilizers	Without
Operating Temperature Range	-65 – 105
UL Flammability Rating	UL 94V-0
Approved Standards	CSA LR7189, UL E28476
Strain Relief	Without
Contact Type	Pin
High Temperature Housing	No
Contact Base Material	Phosphor Bronze
Termination End Plating Material	Tin-Lead Over Nickel
Board Standoff	Without
Panel Mount Retention	Without
Keyed	No
Solder Tail Contact Plating Material	Tin-Lead over Nickel
Packaging Method	Carton
Product Type	Connector
Selectively Loaded	No
Gasket	Without
Contact Mating Area Plating Material	Tin-Lead
High Speed Serial Data Connector	No
Termination Method to PC Board	Through Hole
Mating Connector Lock	Without
Contact Current Rating	3

Product Type Features

Applies To	Printed Circuit Board
Connector Style	Plug
PCB Mounting Orientation	Vertical
Connector Type	Header
Row-to-Row Spacing	2.54 mm [.1 in]

Configuration Features

Number of Positions	2
Number of Rows	1

Body Features

Header Type	Breakaway
-------------	------------------

Mechanical Attachment

PCB Mounting Style

Through Hole

Housing Features

Centerline

2.54 mm [.1 in]

Product Compliance

[Statement of Compliance](#)

PDF

[VIEW ALL PRODUCT COMPLIANCE](#)