

## Ƴ ⊡ f ▼



✓ Active



TE CONNECTIVITY (TE) 6PCV-20-720=6PCV ASSEMBLY Buchanan

2-1437654-7 TE Internal Number: 2-1437654-7 Alias ID: 6PCV-20-720

## Always EU RoHS/ELV Compliant

Barrier Style **Tri-Barrier** Bottom Termination Style **Printed Circuit Pin** Current Rating (A) **5, 25** Centerline **9.53 mm [.375 in ]** 

Number of Positions 20

Product Drawings

## 6PCV-XX-007 ASSEMBLY PDF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Block Style Product Type Applies To	Open Bottom with Standoffs Barrier Strip Printed Circuit Board
Configuration Features	Number of Positions Number of Rows Number of Levels	20 1 1
Electrical Characteristics	Current Rating (A) Voltage (V) Current Rating (Max) (A)	5, 25 300, 600 25
Body Features	Barrier Style Color	Tri-Barrier Black

	Terminal Plating Finish Terminal Plating Material	Bright Tin
Termination Features	Bottom Termination Style	Printed Circuit Pin
Mechanical Attachment	Top Hardware	Binding Combo Head
	Mounting Options	None
	Screw Material	Steel
	Screw Plating Material	Zinc Chromate
	Mounting Insert	Without
	Mounting Angle	Vertical
	Mounting Style	Direct (All Positions Filled)
	Mounting Ears	Without
	Screw Size	6-32
Housing Features	Centerline	9.53 mm [ .375 in ]
	Housing Material	Thermoplastic
Dimensions	Wire Range	22 – 12 AWG [ .3 – 3 mm² ]
	Length	192.05 mm [ 7.561 in ]
Usage Conditions	Operating Temperature Range	105 °C [ 221 °F ]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	35
	Packaging Method	Package
Other	Comment	Other options available upon request, consult our Product Information Center.
Product Compliance	Statement of Compliance PDF	

VIEW ALL PRODUCT COMPLIANCE