



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

ULTRAFAST 250 ASSY REC 16-14 TPBR LP

Ultra-Fast | 250

3-350820-2

TE Internal Number: 3-350820-2

Alias ID: 110239, 4-16211-4789, 402014575, A06502-000, AMPS-3-0350820-2

Always EU RoHS/ELV Compliant

Mating Tab Width **6.35 mm [.25 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter (Max) **4.06 mm [.16 in]**

Wire Size (AWG) **16 – 14**

Wire Size (mm²) **1.31 – 2.08**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[RECEPTACLE ASSY,ULTRA-FAST, LOOSE PIECE,,250 SERIES,16-14 AWG](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[Ultra-Fast And Ultra Fast Plus](#)

PDF
English

Product Specifications

Product Specification

[Ultra-Fast Fully Insulated FASTON Receptacle Terminals](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_3-350820-2_111120152052_dmtec](#)

PDF
English

Product Type Features	Wire Stop	Yes
	Disconnect Type	Quick Disconnect Pin
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Wire/Cable Type	Discrete Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
	Terminal Angle	Straight
Electrical Characteristics	Voltage (Max) (V)	600
Body Features	Plating Material	Tin
	Fully Insulated	Yes
Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin
Termination Features	Crimp Type	F-Crimp
Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter (Max)	4.06 mm [.16 in]
	Wire Size (AWG)	16 – 14
	Wire Size (mm ²)	1.31 – 2.08
	Overall Length	21.755 mm [.855 in]
Usage Conditions	Operating Temperature Range (°C)	105
Industry Standards	UL Rating	Listed
	UL Flammability Rating	UL 94V-2
Packaging Features	Packaging Method	Loose Piece

Packaging Quantity

1000

Other

Barrel Color





Blue

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	STANDARD POWER RELAYS	SURFACE MOUNT RESISTORS	SCREENED BACKSHELLS/ADAPTERS
			
250 ULTRA-FAST TAB 16-14 TPBR 3-520107-2	RTH34012WG 1-1415536-9	CPF 0603 52R3 0.1% 25PPM 1K RL CPF0603B52R3E1	TXR40AB00-1208BI TXR40AB00-1208BI
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products