



BOARD-TO-BOARD HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)

16 MODII HORZ DR CE EESS .100

AMPMODU | AMPMODU

1-535512-8

TE Internal Number: 1-535512-8

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Connector Style **Receptacle**

Centerline **2.54 mm [.1 in]**

Number of Positions **16**

Packaging Method **Tube, Tube/Box**

Contact Mating Area Plating Material **Gold**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[AMPMODU MOD II RECEPTACLE ASSEMBLY, HORIZONTAL, .100 CL, 2 ROW, CLOSED-ENTRY, SHORT POINT OF CONTACT, END-TO-END STACKABLE](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[3D PDF](#)

PDF
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

Product Specifications

Application Specification

[AMPMODU Mod II And Mod IV Printed Circuit Board Connectors](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style	Receptacle
PCB Mounting Orientation	Right Angle
Row-to-Row Spacing (mm)	2.54, 7.87
Row-to-Row Spacing (in)	.31

	Applied Pressure	High, Standard
	Profile	Standard
	Product Type	Connector
	Applies To	Printed Circuit Board
	Boss	Without
	Series	AMPMODU, MOD II
	Sealed	No
	Connector Type	Connector Assembly
<hr/>		
Configuration Features	Number of Positions	16
	Number of Rows	2
	Stackable	Yes
<hr/>		
Electrical Characteristics	Voltage (VAC)	333
	Contact Resistance (M Ω)	12
	Insulation Resistance (M Ω)	5000
	Dielectric Withstanding Voltage (VAC)	750
<hr/>		
Contact Features	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (μ in)	30
	Contact Current Rating (A)	2
	Contact Type	Socket
	Contact Configuration	Short Point
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Solder Tail Contact Plating Thickness (μ m)	1.27
	Contact Base Material	Phosphor Bronze
<hr/>		
Termination Features	Termination Method to PC Board	Through Hole - Solder
	Termination Post Length	2.92 mm [.115 in]
<hr/>		
Mechanical Attachment	PCB Mount Retention	Without
<hr/>		
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Polyester - GF
	Housing Color	Black
	Housing Entry Style	Closed Entry, Side
<hr/>		

Dimensions	Mating Post Length	3 mm [.1 in]
	Height	6.05 mm [.238 in]
	PCB Thickness (Recommended)	1.4 – 2.4 mm [.055 – .094 in]
	Tail Length (mm)	2.92
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Compatible	Yes
Operation/Application	Pick and Place Cover	Without
	Assembly Process Feature	Board Standoff
	For Use With	Mates with Headers
Industry Standards	UL Flammability Rating	UL 94V-0
	MIL-C-55032	No
	Approved Standards	CSA LR7189, UL E28476
Packaging Features	Packaging Method	Tube, Tube/Box
	Packaging Quantity	28
Other	Comment	6.50 [.256] minimum positive pin stop to prevent shorting between rows., TE recommends mating gold or duplex plated headers with duplex plated receptacle assemblies.
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	