


SPLICES





✓ Activ

<u>±</u>

PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)
WIRE CAP, RED 22-18

Closed End Splice

328307

TE Internal Number: 328307 Mil-Spec: MS25274-2

Always EU RoHS/ELV Compliant

Product Type Splice Accessory

Sealed No

Wire Insulation Diameter (Max) 3.15 mm [.124 in]

Wire Size (AWG) **22 - 18**

Wire Size (CMA) 509 - 3248

Product Drawings SPARE WIRE CAP, WIRE SIZE, 22-18 AWG

PDF **English**

CAD Files 3D PDF

PDF **English**

Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP **English**

Customer View Model

3D_STP.ZIP English

Product Specifications

Application Specification Pre-Insulated Diamond Grip (PIDG) Terminals, Splices, And End Caps

PDF **English**

Product Environmental Compliance

TE Material Declaration MD_328307_07282011726

PDF **English**

Instruction Sheets

Instruction Sheet (U.S.) Spare Wire Caps 328307, 328308, And 328309

PDF English

Product Type Features	Product Type	Splice Accessory
Troduct type readines		
	Sealed	No
	Serrated	Yes
	Accessory Type	Wire Cap
	Wire/Cable Type	Stripped Wire
	Insulated	Yes
	Support Style	Insulation Support
Configuration Features	Number of Serrations	12
Body Features	Splice Material	Copper
	Color	Red
	Insulation Material	Nylon
	Plating Material	Tin
	Insulation Type	Pre-Insulated
Contact Features	Class	1 & 2
Dimensions	Wire Insulation Diameter (Max)	3.15 mm [.124 in]
	Wire Size (AWG)	22 – 18
	Wire Size (CMA)	509 - 3248
	Wire Size (mm²)	.39
	Overall Length	11.303 mm [.445 in]
Usage Conditions	Operating Temperature (Max)	105°C [221°F]
Industry Standards	Government Qualified	Yes
	Military Category	Yes
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	1000
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

