

CRIMP RINGS & SPADES





✓ Active



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

TERMINAL, SOLIS R HR 12-10 8

SOLISTRAND | SOLISTRAND

323061

TE Internal Number: 323061

Always EU RoHS/ELV Compliant

Terminal Shape Ring Tongue

Stud Diameter 4.34 mm [.171 in]

Tongue Thickness 1.07 mm [.042 in]

Sealed No

Heavy Duty No

Product Drawings TERMINAL, RING TONGUE, HEAT RESISTANT, STRATO-THERM

PDF **English**

CAD Files 3D PDF

PDF **English**

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP English

Customer View Model

2D_DXF.ZIP **English**

Product Specifications

Product Specification Nickel Plated SOLISTRAND STRATO-THERM Terminals

PDF **English**

Product Environmental Compliance

TE Material Declaration MD_323061_08252015941_dmtec

PDF **English**

Instruction Sheets

Instruction Sheet (U.S.) Heat Resistant Terminal Kits

PDF **English**

Product Type Features	Sealed	No
	Barrel Type	Closed Barrel
	Wire/Cable Type	Regular Wire
	Insulated	No
	Insulated Wire Support	No
	Stud Size	8, M4
	Shape Code	RING-084
	Wire/Cable Composition	Solid or Stranded
Configuration Features	Terminal Angle	Straight
	Number of Holes	1
Body Features	Plating Material	Copper, Nickel
	Plating Thickness	7.62 µm [300 µin]
	Inspection Slot	No
	Weight per Piece (g)	1.512
Contact Features	Terminal Shape	Ring Tongue
	Terminal Orientation	Straight
Dimensions	Stud Diameter	4.34 mm [.171 in]
	Tongue Thickness	1.07 mm [.042 in]
	Wire Size (AWG)	12 – 10
	Wire Size (mm²)	2.62 - 6.64
	Wire Size (CMA)	5180 – 13100
	Overall Length	19.43 mm [.765 in]
	Barrel Inside Diameter (Min)	3.28 mm [.129 in]
Usage Conditions	High Temperature Rating	343 °C [650 °F]
	Operating Temperature Range (°C)	343
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No

Packaging Features Packaging Method Loose Piece

Packaging Quantity

500

Product Compliance

Statement of Compliance

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

