



CRIMP RINGS & SPADES



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

PIDG R 22-16 COMM 22-18 MIL 4

[PIDG](#) | [PIDG](#)

323758

TE Internal Number: 323758

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **3.02 mm [.119 in]**

Tongue Thickness **.78 mm [.031 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

[TERMINAL, RING TONGUE,PIDG\(TM\), WIRE SIZE, 22-16 AWG](#)

PDF (**TIFF AVAILABLE**)
English

[TERMINAL, RING TONGUE,PIDG\(TM\), WIRE SIZE, 22-16 AWG](#)

PDF (**TIFF AVAILABLE**)
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[1773464-1_QRG_PIDG_TERMINALS_AND_SPLICES](#)

PDF
English

Product Specifications

Application Specification

[Pre-Insulated Diamond Grip \(PIDG\) Terminals, Splices, And End Caps](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_323758_07042014915_dmtec](#)

PDF
English


Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Sealed	No
	Barrel Type	Closed Barrel
	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Stud Size	4, M2.5
	Shape Code	RING-041
	Wire/Cable Composition	Solid or Stranded
Configuration Features	Terminal Angle	Straight
	Number of Holes	1
Electrical Characteristics	Voltage (Max) (V)	300
Body Features	Plating Material	Copper, Tin
	Insulation Sleeve Material	Nylon
	Insulation Material	Nylon
	Inspection Slot	No
	Weight per Piece (g)	.739
	Insulation Type	Pre-Insulated
Contact Features	Terminal Shape	Ring Tongue
	Terminal Orientation	Straight
Dimensions	Stud Diameter	3.02 mm [.119 in]
	Tongue Thickness	.78 mm [.031 in]
	Wire Insulation Diameter (Max)	3.18 mm [.125 in]
	Wire Insulation Diameter	2.03 – 3.175 mm [.08 – .125 in]
	Wire Size (AWG)	22 – 16
	Wire Size (mm²)	.26 – 1.65
	Wire Size (CMA)	509 – 3260
	Overall Length	21.44 mm [.8441 in]

Usage Conditions	Operating Temperature Range (°C)	105
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	1000
Other	Barrel Color	Red
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

CRIMP RINGS & SPADES



PIDG R 22-16 COMM 22-18 MIL 8
6-320551-1

Save to List

Find Similar Products


CRIMP QUICK DISCONNECTS

250 ULTRA-FAST TAB 16-14 TPBR
3-520106-2

Save to List

Find Similar Products

CRIMP RINGS & SPADES




PIDG R 22-16 COMM 22-18 MIL 2
328657

Save to List

Find Similar Products

SOLDERSLEEVE SHIELD TERMINATORS



SO63-3-00
SO63-3-00

Save to List

Find Similar Products