



HEADERS & RECEPTACLES



TE CONNECTIVITY (TE) 10P MTA100 CONN ASSY POL RIB [MTA | MTA-100](#)

1-643813-0
TE Internal Number: 1-643813-0

[Not EU RoHS or ELV Compliant](#)
[Find Compliant Alternatives](#)

Centerline **2.54 mm [.1 in]**

Number of Positions **10**

Number of Rows **1**

Contact Mating Area Plating Material **Tin-Lead**

Contact Mating Area Plating Material Finish **Bright**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[MTA 100 CONNECTOR ASSEMBLY, 22 AWG, STANDARD](#)
PDF
English

CAD Files

[Customer View Model](#)
2D_DXF.ZIP
English

[3D PDF](#)
PDF
3D

[Customer View Model](#)
3D_IGS.ZIP
English

[Customer View Model](#)
3D_STP.ZIP
English

Catalog Pages/Data Sheets

[MTA, CST-100 II, SL-156 And AMP Economy Power \(EP\) Connectors](#)
PDF
English

Product Environmental Compliance

TE Material Declaration [MD_1-643813-0_05282015329_dmtec](#)
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Connector

Connector Type

Connector Assembly

Connector System

Wire to Board





	Connector System	wire-to-post
	Wire/Cable Type	Discrete Wire, Stranded
	Strain Relief	With
	Sealed	No
	Connector Style	Receptacle
	Applies To	Wire/Cable
	Connector Design	Closed End
<hr/>		
Configuration Features	Number of Positions	10
	Number of Rows	1
	Backwall/Post Interruptions	Without
<hr/>		
Electrical Characteristics	Operating Voltage (VAC)	250
<hr/>		
Body Features	Cable Exit Angle	90°
<hr/>		
Contact Features	Contact Mating Area Plating Material	Tin-Lead
	Contact Mating Area Plating Material Finish	Bright
	Contact Mating Area Plating Thickness	2.03 – 5.08 µm [80 – 200 µin]
	Contact Termination Area Plating Thickness	2.03 µm [80 µin]
	Contact Termination Area Plating Material	Tin-Lead
	Contact Type	Socket
	Contact Transmits (Typical)	Power
	Contact Current Rating (A)	5
	Contact Layout	Inline
	Contact Termination Area Plating Material Finish	Bright
Contact Base Material	Copper Alloy	
<hr/>		
Termination Features	Termination Method to Wire/Cable	IDC
<hr/>		
Mechanical Attachment	PCB Mount Alignment	Without
	Mating Retention	With
	PCB Mount Retention	Without
	Contact Retention	With
	Mating Alignment Type	Polarization
	Contact Retention Type	Locking Lance
	Mating Retention Type	Locking Ramp

	Panel Mount Retention	Without
	Mating Alignment	With
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	White
	Housing Style	Standard
	Housing Material	Nylon - GF
Dimensions	Wire/Cable Size (AWG)	22
	Wire/Cable Size (mm ²)	.3 – .4
	Insulation Diameter	1.52 mm [.06 in]
	Length (mm)	25.4
	Height (mm)	6.99
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	For Use With	MTA .100 Header
	Pick and Place Cover	Without
Industry Standards	UL Flammability Rating	UL 94V-2
	UL File Number	E28476
	CSA Rating	Certified
	Agency/Standard	CSA, UL
	CSA File Number	LR7189
	UL Rating	Recognized
Packaging Features	Packaging Method	Bag/Box
	Packaging Quantity	500
Other	Comment	Stripe may run down between ribs

Product Compliance [Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>AUTOMOTIVE CONNECTOR CAPS & COVERS</p>  <p>COVER ASSY 96 POS. 1452389-1</p> <p>Save to List Find Similar Products</p>	<p>MOTOR TERMINAL HOUSINGS</p>  <p>HOUSING 4P .110 FASTIN-ON REC. 626056</p> <p>Save to List Find Similar Products</p>	<p>CRIMP QUICK DISCONNECTS</p>  <p>FASTON RECEP 6, 35 735209-2</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>06P UMNL PLUG HSG 150C BLK 794535-1</p> <p>Save to List Find Similar Products</p>
---	---	---	--

Products - 35 Results

[View All](#)

[Compare 0/10](#)


Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - W-T-B Headers & Receptacles MTA MTA-100</p> <p>10P MTA-100 HDR ASSY, SM, SN - 4-647106-0 TE INTERNAL NUMBER: 4-647106-0</p> <p>✓ Active</p> <p>Always EU RoHS/ELV Compliant</p> <p>Centerline 2.54 mm</p> <p>Number of Positions 10</p> <p>PCB Mounting Orientation Vertical</p> <p>PCB Mounting Style Through Hole</p> <p>Number of Rows 1</p>
---	--

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - W-T-B Headers & Receptacles MTA MTA-100</p> <p>10P MTA100 HDR ASSY F/L LF - 4-647609-0 TE INTERNAL NUMBER: 4-647609-0</p> <p>✓ Active</p> <p>Always EU RoHS/ELV Compliant</p> <p>Centerline 2.54 mm</p> <p>Number of Positions 10</p> <p>PCB Mounting Orientation Vertical</p> <p>PCB Mounting Style Through Hole</p> <p>Number of Rows 1</p>
---	--


RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - W-T-B Headers & Receptacles
MTA | MTA-100

**10P MTA100 HDR ASSY,
SM, FL, LF - 4-647166-0**

TE INTERNAL NUMBER: 4-647166-0

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**

Number of Positions **10**

PCB Mounting Orientation

Vertical

PCB Mounting Style **Surface**

Mount

Number of Rows **1**