



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

FF FLACHSTECKER 2,8

FASTON | FASTON Terminals and Housings

160743-4

TE Internal Number: 160743-4

Always EU RoHS/ELV Compliant

Terminal Style **Tab**

Mating Tab Width **2.79 mm [.11 in]**

Mating Tab Thickness **.79 mm [.031 in]**

Wire Insulation Diameter (Max) (mm) **3**

Wire Insulation Diameter **2.3 – 3 mm [.091 – .118 in]**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[FASTIN-FASTON Conns. .110 Sr. Tab Ctc.](#)

PDF (TIFF AVAILABLE)
English

[FASTIN-FASTON Conns. .110 Sr. Tab Ctc.](#)

PDF (TIFF AVAILABLE)
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[FASTIN_FASTON_Product_Line](#)

PDF
English

Product Specifications

Application Specification

[FASTIN FASTON TAB AND RECEPTACLE CONTACT APPLICATION SPECIFICATION](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Wire Stop	No
	Disconnect Type	Quick Disconnect
	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Type	Regular Wire
	Insulated	No
	Insulated Wire Support	Yes
	Support Style	Insulation Support
Applies To	Wire/Cable	
<hr/>		
Configuration Features	Paired	No
	Stud Hole	No
	Terminal Angle	Straight
	Connection Capacity	Single
<hr/>		
Body Features	Plating Material	Brass, Tin
	Fully Insulated	No
<hr/>		
Contact Features	Terminal Style	Tab
	Terminal Orientation	Straight
	Contact Plating Material	Pre-Tin
<hr/>		
Termination Features	Crimp Type	F-Crimp
<hr/>		
Mechanical Attachment	Mating Retention Type	Locking Lance
	Locking Lance Height (mm)	1.1
<hr/>		
Dimensions	Mating Tab Width	2.79 mm [.11 in]
	Mating Tab Thickness	.79 mm [.031 in]
	Wire Insulation Diameter (Max) (mm)	3
	Wire Insulation Diameter	2.3 – 3 mm [.091 – .118 in]
	Wire Size (AWG)	20 – 15
	Wire Size (mm ²)	.5 – 1.5
	Material Thickness	.4 mm [.016 in]
	Overall Length	22 mm [.866 in]
<hr/>		
Operation/Application	For Housing Type	Single or Multiple





Packaging Features	Packaging Method	Reel
	Packaging Quantity	6000
Other	Comment	According to DIN 46343, Part 1

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	FPC CONNECTORS	AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD TERMINALS	MOTOR TERMINAL HOUSINGS
 <p>GDS-FLACHST 2, 8X0, 8 1-725996-2</p> <p>Save to List Find Similar Products</p>	 <p>FPC CONN. 0.5MM PITCH B/C, 34P 3-1734592-4</p> <p>Save to List Find Similar Products</p>	 <p>AMP MCP 1.5K, CONTACT 1534334-1</p> <p>Save to List Find Similar Products</p>	 <p>16 POS. ISO TAB HSG 338696-1</p> <p>Save to List Find Similar Products</p>