




CRIMP RINGS & SPADES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

TERMINAL,PIDG SPD 12-10 6

PIDG

2-326859-1

TE Internal Number: 2-326859-1

Always EU RoHS/ELV Compliant

Terminal Shape **Spade Tongue**

Stud Diameter **3.68 mm [.145 in]**

Tongue Thickness **1.02 mm [.04 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

[WIRE TERMINAL P.I.D.G-SPADE, WIRE SIZE 12-10](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.









Product Type Features

Sealed	No
Barrel Type	Closed Barrel
Wire/Cable Type	Regular Wire
Insulated	Yes
Insulated Wire Support	Yes
Support Style	Insulation Support
Stud Size	6, M3.5
Shape Code	SPADE-020

	Wire/Cable Composition	Solid or Stranded
Configuration Features	Terminal Angle	Straight
Electrical Characteristics	Voltage (Max) (V)	300
Body Features	Plating Material	Copper, Tin
	Insulation Sleeve Material	Copper
	Insulation Material	Nylon
	Inspection Slot	No
	Weight per Piece (g)	2.373
	Insulation Type	Pre-Insulated
Contact Features	Terminal Shape	Spade Tongue
	Terminal Orientation	Straight
Dimensions	Stud Diameter	3.68 mm [.145 in]
	Tongue Thickness	1.02 mm [.04 in]
	Wire Insulation Diameter (Max)	5.84 mm [.23 in]
	Wire Insulation Diameter (in)	.15 – .23
	Wire Size (AWG)	12 – 10
	Wire Size (mm ²)	2.62 – 6.64
	Wire Size (CMA)	5180 – 13100
	Overall Length	27.81 mm [1.0949 in]
Usage Conditions	Operating Temperature Range (°C)	105
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Tape Mounted
	Packaging Quantity	2500
Other	Barrel Color	Yellow

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	STANDARD POWER RELAYS	STANDARD POWER RELAYS	CRIMP QUICK DISCONNECTS
250 FAST RCPT 14-10 018BR 60635-3	KRPA-11DN-12=KRPA KRPA-11DN-12	KUEP-3D15-24=KU- KUEP-3D15-24	.250 FAST REC IS 18-14 TPBR 41274
 Save to List  Find Similar Products	 Save to List  Find Similar Products	 Save to List  Find Similar Products	 Save to List  Find Similar Products