




## CRIMP RINGS & SPADES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### TERMINAL,PIDG SPD 16-14 8

PIDG

2-321233-1

TE Internal Number: 2-321233-1

Always EU RoHS/ELV Compliant

Terminal Shape **Spade Tongue**

Stud Diameter **4.34 mm [ .171 in ]**

Tongue Thickness **.79 mm [ .031 in ]**

Sealed **No**

Heavy Duty **No**

#### Product Drawings

[TERMINAL, SPADE, PIDG, WIRE SIZE: 16-14](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

#### Product Type Features

Sealed	<b>No</b>
Barrel Type	<b>Closed Barrel</b>
Wire/Cable Type	<b>Regular Wire</b>
Insulated	<b>Yes</b>
Insulated Wire Support	<b>Yes</b>
Support Style	<b>Insulation Support</b>
Stud Size	<b>8, M4</b>
Shape Code	<b>SPADE-020</b>












	Barrel Style	Standard
Electrical Characteristics	Voltage (Max) (V)	<b>300</b>
Body Features	Plating Material	<b>Copper, Tin</b>
	Insulation Material	<b>Nylon</b>
	Weight per Piece (g)	<b>.928</b>
	Insulation Type	<b>Pre-Insulated</b>
Contact Features	Terminal Shape	<b>Spade Tongue</b>
	Terminal Orientation	<b>Straight</b>
Dimensions	Stud Diameter	<b>4.34 mm [ .171 in ]</b>
	Tongue Thickness	<b>.79 mm [ .031 in ]</b>
	Wire Insulation Diameter (Max) (mm)	<b>4.32</b>
	Wire Insulation Diameter	<b>2.92 – 4.31 mm [ .1149 – .1696 in ]</b>
	Wire Size (AWG)	<b>16 – 14</b>
	Wire Size (mm <sup>2</sup> )	<b>1.25 – 2</b>
	Wire Size (CMA)	<b>2050 – 5180</b>
	Overall Length (mm)	<b>19.13</b>
	Barrel Inside Diameter (Min) (in)	<b>.173</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-40 – 105</b>
Operation/Application	Heavy Duty	<b>No</b>
Industry Standards	Government Qualified	<b>No</b>
Packaging Features	Packaging Method	<b>Tape Mounted</b>
	Packaging Quantity	<b>5000</b>
Other	Barrel Color	<b>Blue</b>

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

# CUSTOMERS ALSO BOUGHT

SMA CONNECTORS	D-SUB CONNECTOR CONTACTS	CRIMP RINGS & SPADES	SPLICES
			
<p>BULKHEAD JACK, SMA, HEX CRIMP 447650-3</p>	<p>SKT CONTACT ASSY 211161-1</p>	<p>PG SPD 22-16 COMM 22- 18 MIL 8 2-34155-1</p>	<p>PG BUTT SPLC 22- 16COMM22-18MIL 1-34070-1</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>