

## **HEADERS & RECEPTACLES**



















**PRODUCT DRAWING** 



3D PDF

TE CONNECTIVITY (TE)

05P MTA100 HDR ASSY FL 30AU LF

MTA | MTA-100

3-641215-5

TE Internal Number: 3-641215-5

Always EU RoHS/ELV Compliant

Centerline 2.54 mm [.1 in]

Number of Positions 5

PCB Mounting Orientation Vertical

PCB Mounting Style Through Hole

Number of Rows 1

**Product Drawings** 

MTA-100 HEADER ASSEMBLY, FRICTION LOCK, NOTCHED, .025 SQUARE

STRAIGHT POST, .000030 GOLD PLATED

PDF English

**CAD Files** 

**Customer View Model** 

2D\_DXF.ZIP English

3D PDF

**Customer View Model** 3D\_IGS.ZIP English

**Customer View Model** 

3D\_STP.ZIP English

Catalog Pages/Data Sheets

MTA, CST-100 II, SL-156 And AMP Economy Power (EP) Connectors

PDF **English** 

**Product Specifications** 

**Product Specification** Connector, MTA-100

PDF **English** 

Product Environmental Compliance

TE Material Declaration MD\_3-641215-5\_063020152337\_dmtec

PDF English

Product Type Features	PCB Mounting Orientation	Vertical
	Product Type	Connector
	Connector Type	Header
	Connector System	Wire-to-Board
	Strain Relief	Without
	Sealed	No
	Connector Style	Plug
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	5
	Number of Rows	1
	Backwall/Post Interruptions	Without
Electrical Characteristics	Operating Voltage (VAC)	250
Body Features	Header Type	Unshrouded
Contact Features	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness	.76 μm [ 29.92 μin ]
	Underplate Material	Nickel
	Contact Termination Area Plating Thickness	3.81 – 8.89 µm [ 150 – 350 µin ]
	Underplate Material Thickness	1.27 μm, 50 μin
	Contact Style	Straight
	Contact Shape	Square
	Tail Plating Material	Tin
	Contact Termination Area Plating Material	Tin
	Tail Plating Thickness	3.81 – 8.89 µm [ 150 – 350 µin ]
	Contact Type	Pin
	Contact Current Rating (A)	5
	Contact Layout	Inline
	Contact Termination Area Plating Material Finish	Matte
	Contact Base Material	Copper Alloy
		··· · · · · · · · · · · · · · · · · ·
Termination Features	Termination Method to PC Board	Through Hole - Solder
	Termination Method to Wire/Cable	Solder

Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Alignment	Without
	Mating Retention	With
	PCB Mount Retention	Without
	Contact Retention	Without
	Mating Retention Type	Friction Lock
	Panel Mount Retention	Without
	Mating Alignment	Without
Housing Features	Centerline	2.54 mm [ .1 in ]
.outg . outu.ou	Housing Color	White
	Housing Style	Friction Lock
	Housing Material	Polyester - GF
Dimensions	Tail Length	3.56 mm [ .14 in ]
	Mating Post Length	7.49 mm [ .295 in ]
	PCB Thickness (Recommended)	1.6 mm [ .063 in ]
	Height	7.87 mm [ .31 in ]
	Length	12.7 mm [ .5 in ]
Jsage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	For Use With	MTA .100 Connector Assembly
	Pick and Place Cover	Without
ndustry Standards	UL Flammability Rating	UL 94V-0
ndustry Standards	UL Flammability Rating UL File Number	UL 94V-0 E28476
ndustry Standards		
ndustry Standards	UL File Number	E28476
ndustry Standards	UL File Number CSA Rating	E28476 Certified
ndustry Standards	UL File Number  CSA Rating  Agency/Standard	E28476  Certified  CSA, UL
ndustry Standards	UL File Number  CSA Rating  Agency/Standard  CSA File Number	E28476  Certified  CSA, UL  LR7189

## VIEW ALL PRODUCT COMPLIANCE

Products - 18 Results

View All

Compare 0/10

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles MTA | MTA-100

05P MTA100 CONN ASSY LF - 3-644044-5 TE INTERNAL NUMBER: 3-644044-5

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm** 

Number of Positions 5

Number of Rows 1

Contact Mating Area Plating

Material Gold

Contact Mating Area Plating

Thickness .76  $\mu m$ 

RELATIONSHIP

Mating Products
Used to identify Mating Parts

See All Mating Products

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles

05P MTA100 CONN ASSY BLU 30AU - 641239-5

TE INTERNAL NUMBER: 641239-5

✓ Active

Always EU RoHS/ELV Compliant

Centerline 2.54 mm

Number of Positions 5

Number of Rows 1

Contact Mating Area Plating

Material Gold

Contact Mating Area Plating

Thickness .76 µm

RELATIONSHIP

Mating Products
Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles MTA | MTA-100

05P MTA100 CONN ASSY F/T LF - 3-644702-5 Always EU RoHS/ELV Compliant

Centerline 2.54 mm

Number of Positions **5** 



TE INTERNAL NUMBER: 3-644702-5

✓ Active

Number of Rows 1

Contact Mating Area Plating

Material **Gold** 

Contact Mating Area Plating

Thickness .76 μm