



BOARD-TO-BOARD HEADERS & RECEPTACLES



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

40 MODII VRT DR CE 100/115

[AMPMODU](#) | [AMPMODU](#)

2-534206-0

TE Internal Number: 2-534206-0

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Connector Style **Receptacle**

Centerline **2.54 mm [.1 in]**

Number of Positions **40**

Packaging Method **Tube, Tube/Box**

Contact Mating Area Plating Material **Gold**

Product Drawings

[RECEPTACLE ASSEMBLY, MOD II, DOUBLE ROW, DUAL ENTRY, .100X.100CL, VERTICAL MOUNT, AMPMODU](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

Product Specifications

Application Specification

[AMPMODU Mod II And Mod IV Printed Circuit Board Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-534206-0_10092015739_dmtec](#)

PDF
English


Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	PCB Mounting Orientation	Vertical
	Row-to-Row Spacing	2.54 mm [.1 in]
	Applied Pressure	Standard
	Profile	Standard
	Product Type	Connector
	Applies To	Printed Circuit Board
	Series	AMPMODU, MOD II
	Sealed	No
	Connector Type	Connector Assembly
Configuration Features	Number of Positions	40
	Number of Rows	2
	Stackable	Yes
Electrical Characteristics	Voltage (VAC)	333
	Contact Resistance (MΩ)	12
	Insulation Resistance (MΩ)	5000
Contact Features	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (μin)	30
	Contact Shape	Square
	Contact Current Rating (A)	2
	Contact Type	Socket
	Contact Configuration	Short Point
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Solder Tail Contact Plating Thickness (μin)	150
	Contact Base Material	Phosphor Bronze
Termination Features	Termination Method to PC Board	Through Hole - Solder
	Termination Post Length	2.92 mm [.115 in]
Mechanical Attachment	PCB Mount Retention	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Polyester - GF
	Housing Color	Black
	Housing Entry Style	Closed Entry, Top

Dimensions	Height	5.03 mm [.198 in]
	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Tail Length (mm)	2.92
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Compatible	No
Operation/Application	Assembly Process Feature	Board Standoff
	For Use With	Mates with Headers
Industry Standards	UL Flammability Rating	UL 94V-0
	MIL-C-55032	No
	Approved Standards	CSA LR7189, UL E28476
Packaging Features	Packaging Method	Tube, Tube/Box
	Packaging Quantity	11
Other	Comment	TE recommends mating gold or duplex plated headers with duplex plated receptacle assemblies., To obtain the minimum mating post length, add 0.51 [.020] (not including the post lead in chamfer) to the maximum point-of-contact dimension.
Product Compliance		
		Statement of Compliance PDF
VIEW ALL PRODUCT COMPLIANCE		

CUSTOMERS ALSO BOUGHT

BOARD-TO-BOARD HEADERS & RECEPTACLES




10 MODII VRT DR CE
100/115
534206-5

Save to List

Find Similar Products

SURFACE MOUNT RESISTORS




CPF 0805 1K5 0.1% 25PPM
1K RL
CPF0805B1K5E1

Save to List

Find Similar Products

THROUGH-HOLE RESISTORS




MPC10 50K 5%
MPC108503J

Save to List

Find Similar Products

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



40 MODII HDR DRST B/A
W/HD
1-104350-7

Save to List

Find Similar Products

