TE Connectivity: Every Connection Counts
© 2015 TE Connectivity Ltd. family of companies. All Rights Reserved

RELAYS, CONTACTORS & SWITCHES

TACTILE SWITCHES



✔ Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

FSM16JAH=6MM TACT SWITCH, HIGH TEMP

Alcoswitch | FSM

3-1825910-2
TE Internal Number: 3-1825910-2
Alias ID: FSM16JAH

Always EU RoHS/ELV Compliant

Actuator Style **Round**

Operating Function **No**

Contact Base Material **Copper Alloy**

Contact Plating **Silver**

Dust Proof **No**

Product Drawings	6MM TACT SWITCH, THRU-HOLE HIGH TEMP PDF **English**
CAD Files	Customer View Model 2D_DXF.ZIP **English** 3D PDF PDF **3D** Customer View Model 3D_IGS.ZIP **English** Customer View Model 3D_STP.ZIP **English**
Catalog Pages/Data Sheets	SWITCHES_CORE_PROGRAM_CATALOG PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Actuator Style	**Round**
	Dust Proof	**No**
	Illuminated	**With**
	Leg Style	**Kinked**
	Product Type	**Switch**

Configuration Features	Operating Function	**No**
	Support Bracket	**Without**
	Configuration (Pole-Throw)	**Single Pole - Single Throw**
	Number of Actuators	**1**
	Ganged	**With**
	ESD Grounding Terminal	**Without**
	Tactile	**Yes**
	Snap Action	**Without**
	Tactile Feel	**With**
Body Features	Actuator Color	**Red**
	Bushing Style	**Unthreaded**
	Actuator Material	**Nylon**
	Actuator Force	**260 g [9.178 oz]**
	Cover Material	**PET Film**
	Actuator Profile	**Extended**
	Case Material	**Nylon**
	Case Color	**Black**
Contact Features	Contact Base Material	**Copper Alloy**
	Contact Plating	**Silver**
	Contact Current Rating (mA)	**50**
Termination Features	Termination Type	**Printed Circuit Board**
Mechanical Attachment	Mounting Type	**Through Hole**
	Mounting Angle	**Vertical**
Housing Features	Low Profile	**With**
	Process Sealed	**No**
Dimensions	Actuator Length	**13.4 mm [.527 in]**
	Switch Height (in)	**.527**
	Button Width	**3.5 mm [.138 in]**
Usage Conditions	Temperature Rating (°C)	**High**

Packaging Features	Packaging Method	**Loose Piece**
Other	Comment	**(On) indicates momentary position.**
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

RIBBON CABLE CONNECTORS

014 LOPRO HDR SP 15DP
103308-2

Save to List
Find Similar Products

SURFACE MOUNT DEVICES

SMD075F-2
SMD075F-2

Save to List
Find Similar Products

TACTILE SWITCHES

FSM4JSMAATR=TACTSWITCH, SMT, T&R
1571563-4

Save to List
Find Similar Products

SURFACE MOUNT RESISTORS

RN 0805 49K9 0.1% 10PPM CUT LE
RN73C2A49K9BTG

Save to List
Find Similar Products