



TACTILE SWITCHES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

FSM18JH=6MM TACT SWITCH, HIGH TEMP

[Alcoswitch](#) | [FSM](#)

3-1825910-5

TE Internal Number: 3-1825910-5

Alias ID: FSM18JH

[Always EU RoHS/ELV Compliant](#)

Actuator Style **Round**

Operating Function **No**

Contact Base Material **Copper Alloy**

Contact Plating **Silver**

Dust Proof **No**

Product Drawings

[6MM TACT SWITCH, THRU-HOLE HIGH TEMP](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SWITCHES_CORE_PROGRAM_CATALOG](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features


| | |
|----------------|---------------|
| Actuator Style | Round |
| Dust Proof | No |
| Illuminated | With |
| Leg Style | Kinked |
| Product Type | Switch |

| | | |
|------------------------|-----------------------------|----------------------------|
| Configuration Features | Operating Function | No |
| | Support Bracket | Without |
| | Configuration (Pole-Throw) | Single Pole - Single Throw |
| | Number of Actuators | 1 |
| | Ganged | With |
| | ESD Grounding Terminal | Without |
| | Tactile | Yes |
| | Snap Action | Without |
| | Tactile Feel | With |
| Body Features | Actuator Color | Black |
| | Bushing Style | Unthreaded |
| | Actuator Material | Nylon |
| | Actuator Force | 160 g [5.648 oz] |
| | Cover Material | PET Film |
| | Actuator Profile | Extended |
| | Case Material | Nylon |
| | Case Color | Black |
| Contact Features | Contact Base Material | Copper Alloy |
| | Contact Plating | Silver |
| | Contact Current Rating (mA) | 50 |
| Termination Features | Termination Type | Printed Circuit Board |
| Mechanical Attachment | Mounting Type | Through Hole |
| | Mounting Angle | Vertical |
| Housing Features | Low Profile | With |
| | Process Sealed | No |
| Dimensions | Actuator Length | 4.9 mm [.193 in] |
| | Switch Height (in) | .335 |
| | Button Width | 3.5 mm [.138 in] |
| Usage Conditions | Temperature Rating (°C) | High |

| | | |
|--------------------|--|------------------------------------|
| Packaging Features | Packaging Method | Loose Piece |
| Other | Comment | (On) indicates momentary position. |
| Product Compliance | Statement of Compliance PDF | |
| | VIEW ALL PRODUCT COMPLIANCE | |

CUSTOMERS ALSO BOUGHT

HIGH FREQUENCY & RF
INDUCTORS




3650 0603 1.6nH 5% 2K RL
36501J1N6JTDG

Save to List

Find Similar Products

SURFACE MOUNT RESISTORS




CPF 0402 69K8 0.1%
25PPM 1K RL
CPF0402B69K8E1

Save to List

Find Similar Products

HIGH FREQUENCY & RF
INDUCTORS




3650 0603 18nH 5% 2K RL
36501J18NJTDG

Save to List

Find Similar Products

TERMINAL BLOCK HEADERS &
RECEPTACLES



TERMI-BLOK PCB MOUNT
35 2P.5
282847-2

Save to List

Find Similar Products

