

RIBBON CABLE CONNECTORS





✓ Active



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

020 UNIV HDR SP 4S 30DP STD L1

AMP-LATCH | Universal Headers

499206-4

TE Internal Number: 499206-4

5 of 6 EU RoHS/ELV Compliant Find Compliant Alternatives

Centerline **2.54 mm [.1 in]**

PCB Mount Retention Without

PCB Mounting Orientation Vertical

Termination Method to PC Board Through Hole - Solder

Shrouded Yes

Product Drawings

HEADER ASSY, UNIVERSAL, AMP-LATCH

PDF **English**

CAD Files

Customer View Model

2D_DXF.ZIP

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP English

3D PDF PDF English

Product Specifications

Product Specification AMP-LATCH And IDC Header Connectors, .100 X .100 Inch Grid

PDF **English**

Qualification Test Report Connector, AMP-LATCH Header, .100 X .100 Inch Grid

PDF **English**

Instruction Sheets

Instruction Sheet (U.S.) AMP INSTALLATION PROCEDURES FOR AMP-LATCH UNIVERSAL HEADER

ASSEMBLIE PDF English

AMP INSTALLATION PROCEDURES FOR AMP-LATCH UNIVERSAL HEADER

ASSEMBLIE

TIF English Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical
	Shrouded	Yes
	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Style	Receptacle
	Profile	Standard
	Applies To	Printed Circuit Board
	Product Type	Connector
	Board Standoff	Without
	Connector Type	Header
	Connector System	Board-to-Board
	Ejection Latches	With
	Latch Type	Long
Configuration Features	Number of Positions	20
	Number of Rows	2
Electrical Characteristics	Operating Voltage (VAC)	250
	Insulation Resistance (M Ω)	5000
Body Features	Post Size	.64 mm [.025 in]
	Header Type	Universal Ejection Pin Headers
	Daisy Chain	Without
Contact Features	Contact Mating Area Plating Material	Gold
	Contact Design	Solder Dip
	Contact Shape	Square
	Contact Transmits (Typical)	Signal (Data)
	Solder Tail Contact Plating Material	Tin-Lead
	Contact Current Rating (A)	1
	Contact Mating Area Plating Thickness (µin)	30
	Contact Type	Pin
	Contact Termination Area Plating Material	Tin, Tin-Lead

Mechanical Attachment	PCB Mount Retention	Without
	Mating Alignment Type	Center, Dual Polarizing Bar
	Mating Connector Lock	With
	Mating Connector Lock Type	Latch
	Mating Alignment	With
	Polarization	With
	Panel Mount Retention	Without
	PCB Mount Alignment	With
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Style	4-Sided
	Housing Material	Thermoplastic
Dimensions	Height	13.94 mm [.55 in]
	PCB Thickness (Recommended)	1.57 mm [.062 in]
Usage Conditions	Temperature Rating	Standard
	Operating Temperature Range (°C)	-65 – 105
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Тгау
	Packaging Quantity	36
Product Compliance	Statement of Compliance	

CUSTOMERS ALSO BOUGHT



VIEW ALL PRODUCT COMPLIANCE

