




# MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## 20 MODII HDR DRST B/A .100CL L

AMPMODU | AMPMODU Headers

6-146256-0

TE Internal Number: 6-146256-0

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [ .1 in ]**

Number of Positions **20**

Header Type **Breakaway**

### Product Drawings

[HEADER ASSEMBLY, MOD , BREAKAWAY, DOUBLE ROW, VERTICAL, HIGH TEMPERATURE](#)

PDF  
English

### CAD Files

[3D PDF](#)

PDF  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

### Product Environmental Compliance

TE Material Declaration

[20 MODII HDR DRST B/A .100CL LF](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Applies To

**Printed Circuit Board**

Connector Style

**Plug**

PCB Mounting Orientation

**Vertical**

Connector Type

**Header**

	Connector Type	<b>Header</b>
	Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
	Stabilizers	<b>Without</b>
	Strain Relief	<b>Without</b>
	Board Standoff	<b>With</b>
	Profile	<b>Standard</b>
	Product Type	<b>Connector</b>
	Gasket	<b>Without</b>
Configuration Features	Number of Positions	<b>20</b>
	Number of Rows	<b>2</b>
	Keyed	<b>No</b>
	Selectively Loaded	<b>No</b>
Electrical Characteristics	Voltage (VAC)	<b>30</b>
	Dielectric Withstanding Voltage	<b>750 V</b>
Body Features	Header Type	<b>Breakaway</b>
	Post Size	<b>.64 mm [ .025 in ]</b>
Contact Features	Contact Protection	<b>Without</b>
	Contact Shape	<b>Square</b>
	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness (µin)	<b>15</b>
	Solder Tail Contact Plating Material Finish	<b>Tin: Matte</b>
	Solder Tail Contact Plating Material	<b>Tin over Nickel</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Current Rating (A)	<b>3</b>
Termination Features	Termination Post Length	<b>3.05 mm [ .12 in ]</b>
	Termination End Plating Thickness (µin)	<b>100 – 200</b>
	Termination End Plating Material	<b>Matte Tin-Lead</b>
	Termination Method to PC Board	<b>Surface Mount, Through Hole</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Retention	<b>Without</b>

Panel Mount Retention	<b>Without</b>
Mating Alignment	<b>Without</b>
Mating Connector Lock	<b>Without</b>

---

Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>

---

Dimensions	PCB Thickness (Recommended)	<b>1.57 mm [ .062 in ]</b>
	Mating Post Length	<b>5.84 mm [ .23 in ]</b>

---

Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
	High Temperature Housing	<b>Yes</b>

---

Operation/Application	High Speed Serial Data Connector	<b>No</b>
-----------------------	----------------------------------	-----------

---

Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>

---

Packaging Features	Packaging Quantity	<b>200</b>
	Packaging Method	<b>Carton</b>

---

Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>
--------------------	---