



# BOARD-TO-BOARD JUMPERS & SHUNTS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## SHUNT, .200 C/L,LP,2 POS, 15AU AMP | L

531230-2

TE Internal Number: 531230-2

Always EU RoHS/ELV Compliant

Shunt Type **Standard Housing**

Shunt Style **Open Top**

Centerline **5.08 mm [.2 in]**

Number of Positions **2**

### Product Drawings

[LOW PROFILE SHUNT CONNECTOR 5.08 \[.200\] CL](#)

PDF  
English

### CAD Files

[3D PDF](#)

PDF  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

### Catalog Pages/Data Sheets

[AMPMODU\\_INTERCONNECTION\\_SYSTEM\\_SECTION\\_6\\_7AND8](#)

PDF  
English

### Product Specifications

Product Specification

[Low Profile Shunt Connector](#)

PDF  
English

Application Specification

[Low Profile, Economy, Dual Beam,And Multiposition Shunt Connectors](#)

PDF  
English

Qualification Test Report

[Low Profile, Economy, Dual Beam,And Multiposition Shunt Connectors](#)

TIF  
English

[Connector, Low Profile Shunt](#)

PDF  
Japanese

[Connector, Low Profile Shunt](#)

TIF  
English

[Connector, Low Profile Shunt](#)

---

## Product Environmental Compliance

TE Material Declaration

[MD\\_531230-2\\_06232014645\\_dmtec](#)  
PDF  
English

---

## Instruction Sheets

Instruction Sheet (U.S.)

[Low Profile, Economy, And Dual Beam Shunt Connectors 382811, 390088, And 382823](#)  
PDF  
English

[Low Profile, Economy, And Dual Beam Shunt Connectors 382811, 390088, And 382823](#)  
TIF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features

Profile

**Low**

Product Type

**Shunt**

---

Configuration Features

Number of Positions

**2**

---

Electrical Characteristics

Insulation Resistance (MΩ)

**1000**

---

Body Features

Handle

**Without**

---

Contact Features

Shunt Type

**Standard Housing**

Shunt Style

**Open Top**

Contact Current Rating (A)

**3**

Contact Base Material

**Beryllium Copper**

Contact Mating Area Plating Thickness

**.381 μm [ 15 μin ]**

Contact Mating Area Plating Material

**Gold**

---

Housing Features

Centerline

**5.08 mm [ .2 in ]**

Housing Material

**Polyester - GF**

Housing Color

**Black**

---

Dimensions

Height

**6.35 mm [ .25 in ]**

---

Usage Conditions

Operating Temperature Range (°C)

**-65 – 105**

Industry Standards	UL Rating	<b>Recognized</b>
	CSA Certified	<b>Yes</b>
	UL Flammability Rating	<b>UL 94V-0</b>


Packaging Features	Packaging Method	<b>Box</b>
	Packaging Quantity	<b>2000</b>

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

TERMINAL BLOCK HEADERS & RECEPTACLES	SURFACE MOUNT RESISTORS	DIP & SIP SWITCHES	RECTANGULAR POWER CONNECTORS
 <p><b>TERMI-BLOK PCB MOUNT 5P</b> 282837-5</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>RLP73K 3A R18 5% 2K RL RLP73K3AR18JTE</b></p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>RIGHT ANGLE DIP SW 8P AU</b> 5435802-1</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>10P MTA156 HDR ASSY STR SQ SN</b> 1-640383-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>