




CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

SUPER SEAL 26POS PLUG ASSY

1473416-1

TE Internal Number: 1473416-1

Always EU RoHS/ELV Compliant

Connector Style **Housing for female terminals**

Mating Pin Diameter **1 mm [.039 in]**

Number of Positions **26**

Pitch **3 mm [.118 in]**

Sealed **Yes**



Product Drawings

[SUPER SEAL CONNECTOR PLUG HOUSING 34Pos. ASS'Y \(DOUBLE\)](#)

PDF
English

[SUPER SEAL CONNECTOR PLUG HOUSING 26POS. ASSEMBLY\(SINGLE\)](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Product Specifications

Product Specification

[SUPER SEAL CONNECTOR](#)

Instruction Sheets

Instruction Sheet (non U.S.)

SUPER SEAL CONNECTOR PLUG HOUSING CONNECTOR
PDF
English

SUPER SEAL CONNECTOR PLUG HOUSING CONNECTOR
TIF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Housing for female terminals

Sealed

Yes

Hybrid Connector

No

Primary Locking Feature

Integrated in Housing

Connector System

Wire-to-Board/Device

Row-to-Row Spacing

4.24 mm [.167 in]

Strain Relief

No

Configuration Features

Number of Positions

26

Number of Rows

4

Electrical Characteristics

Nominal Voltage Architecture (V)

12, 24, 42, 48, 80, 90, 125, 240

Operating Voltage

250 VAC [250 VDC]

Body Features

Cable Exit Angle

180°

Body Material

PBT GF

Color

Black

Contact Features

Mating Pin Diameter

1 mm [.039 in]

Mechanical Attachment

Terminal Position Assurance

Yes

Mounting Feature

No

Polarized

Yes

Housing Features

Pitch

3 mm [.118 in]

Dimensions

Width

32.2 mm [1.268 in]

	Height	34.55 mm [1.36 in]
	Length	32.15 mm [1.266 in]
Usage Conditions	Operating Temperature (Max) (°C)	70, 75, 80, 85, 90, 100, 105, 110, 120, 125
	Operating Temperature (Max) (°F)	158, 167, 176, 185, 194, 212, 221, 230, 248, 257
	Operating Temperature Range	-40 – 125 °C [-40 – 257 °F]
Industry Standards	Degree of Protection	Other
	UL Flammability Rating	UL 94V-2
Packaging Features	Packaging Method	Tube
	Packaging Quantity	20
Other	Connector Position Assurance Capable	No
	Serviceable	Yes

Product Compliance

Statement of Compliance

PDF

VIEW ALL PRODUCT COMPLIANCE

