




BARRIER STRIPS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

4DB-P108-08=4DB ASSEMBLY

Buchanan | 4DB Series

4DB-P108-08

TE Internal Number: 3-1437667-1

Always EU RoHS/ELV Compliant

Barrier Style **Dual Barrier**

Bottom Termination Style **Printed Circuit Pin**

Current Rating (A) **10, 20**

Centerline **8.26 mm [.325 in]**

Number of Positions **8**

Product Drawings

[ASSEMBLY, DUAL BARRIER 4DB P108 XX](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS](#)

PDF
English

[1-1773458-2_BARRIER_STRIPS_QUICK_REFERENCE_GUIDE](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_3-1437667-1_072420141235_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Product Type	Barrier Strip
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	8
	Number of Rows	1
	Number of Levels	1
Electrical Characteristics	Current Rating (A)	10, 20
	Voltage (V)	150, 300
	Current Rating (Max) (A)	20
Body Features	Barrier Style	Dual Barrier
	Color	Black
Contact Features	Terminal Material	Copper Alloy
	Terminal Plating Finish	Bright
	Terminal Plating Material	Tin
Termination Features	Bottom Termination Style	Printed Circuit Pin
Mechanical Attachment	Top Hardware	Wire Clamp Combo Head
	Mounting Options	None
	Screw Material	Steel
	Screw Plating Material	Zinc Chromate
	Mounting Insert	Without
	Mounting Angle	Vertical
	Mounting Style	Direct (All Positions Filled)
	Mounting Ears	Without
	Screw Size	6-32
Screw Head Type	Wire Clamp Combo Head	
Housing Features	Centerline	8.26 mm [.325 in]
	Housing Material	Thermoplastic Polyamide
Dimensions	Wire Range	22 – 12 AWG [.3 – 3 mm²]
	Length	67.69 mm [2.665 in]

Usage Conditions	Operating Temperature Range	105 °C [221 °F]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	24
	Packaging Method	Package
Other	Comment	Do not order screw and captive clamp in combination with other top hardware., Other options available upon request, consult our Product Information Center.

Product Compliance [Statement of Compliance PDF](#)
[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD HEADERS & RECEPTACLES	BARRIER STRIPS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	STANDARD POWER RELAYS
<p>04P MTA100 SHRD HDR ASSY RA FL 2-644803-4</p> <p> Save to List Find Similar Products</p>	<p>4DB-P108-06=4DB ASSEMBLY 4DB-P108-06</p> <p> Save to List Find Similar Products</p>	<p>04 MODII HDR DRST B/A .100CL 103240-2</p> <p> Save to List Find Similar Products</p>	<p>RTE24048F RTE24048F</p> <p> Save to List Find Similar Products</p>