




DIP & SIP SWITCHES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

GDS08S04=DIP SW,SLIDE,SMT

[Alcoswitch](#) | [GDS](#)

1-1825006-5

TE Internal Number: 1-1825006-5

Alias ID: GDS08S04

[Always EU RoHS/ELV Compliant](#)

Product Type **Switch**

Contact Mating Area Plating Material **Gold**

Housing Color **Black**

Housing Material **Polyphenylene Sulfide (PPS)**

Auto-Insertable **Yes**

Product Drawings

[DIP SWITCH ASSEMBLY GDS SERIES](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SWITCHES_CORE_PROGRAM_CATALOG](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1-1825006-5_0130201225](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Switch

Sealed

Yes

Switch Type

DIP

	Switch Type	DIP
	Actuator Style	Slide
Configuration Features	Number of Switches	8
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Positions	8
Electrical Characteristics	Voltage Rating (VDC)	50
Body Features	Seal Type	Tape
	Actuator Color	White
Contact Features	Contact Mating Area Plating Material	Gold
	Auto-Insertable	Yes
	Contact Current Rating (A)	.1
	Contact Base Material	Copper Alloy
	Contact Mating Area Plating Thickness (µin)	10
	Solder Tail Contact Plating	Gold over Nickel
Termination Features	Termination Post Length	4.3 mm [.169 in]
	Termination Style	Outside L
Mechanical Attachment	Mounting Type	Surface Mount
	Mounting Angle	Vertical
Housing Features	Housing Color	Black
	Housing Material	Polyphenylene Sulfide (PPS)
	Centerline	2.54 mm [.1 in]
	Low Profile	Yes
Dimensions	Length	20.17 mm [.794 in]
	Height	2.7 mm [.106 in]
Usage Conditions	Operating Temperature Range (°C)	-30 – 85
Industry Standards	UL Flammability Rating	UL 94V-0

Packaging Features	Packaging Method	Tube
	Packaging Quantity	20


Product Compliance

[Statement of Compliance](#)
PDF


[VIEW ALL PRODUCT COMPLIANCE](#)


CUSTOMERS ALSO BOUGHT

SURFACE MOUNT RESISTORS




CPF 0603 9K1 0.1% 25PPM
1K RL
CPF0603B9K1E1


 Save to List


 Find Similar Products

SURFACE MOUNT RESISTORS




RN 0805 76K8 0.1% 10PPM
1KRL
RN73C2A76K8BTDF


 Save to List


 Find Similar Products

DIP & SIP SWITCHES




GDS04S04=DIP SW, SLIDE,
SMT
1825006-7


 Save to List


 Find Similar Products

SURFACE MOUNT RESISTORS



CPF 0603 4K3 0.1% 25PPM
1K RL
CPF0603B4K3E1

 Save to List

 Find Similar Products

