



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

ADF04STTR04=DIP S,FLUSH,SMT-GW

[Alcoswitch](#) | [AD](#)

ADF04STTR04

TE Internal Number: 1-1825059-8

Alias ID: 1438876

[Always EU RoHS/ELV Compliant](#)

Product Type **Switch**

Contact Mating Area Plating Material **Gold Flash**

Housing Color **Black**

Housing Material **Polyphenylene Sulfide (PPS)**

Auto-Insertable **Yes**

Product Drawings

[DIP SWITCH, ADF-SMT SERIES](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SWITCHES_CORE_PROGRAM_CATALOG](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1-1825059-8_07292013648_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Switch

Sealed

Yes

Switch Type

DIP

	Switch Type	DIP
	Actuator Style	Flush, Slide
Configuration Features	Number of Switches	4
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Positions	4
Electrical Characteristics	Voltage Rating (VDC)	5
Body Features	Seal Type	Tape
	Actuator Color	White
Contact Features	Contact Mating Area Plating Material	Gold Flash
	Auto-Insertable	Yes
	Contact Current Rating (A)	1
	Contact Base Material	Copper Alloy
	Contact Mating Area Plating Thickness (µin)	1.2
	Solder Tail Contact Plating	Nickel
Termination Features	Termination Style	Outside L
Mechanical Attachment	Mounting Type	Surface Mount
Housing Features	Housing Color	Black
	Housing Material	Polyphenylene Sulfide (PPS)
	Centerline	2.54 mm [.1 in]
Dimensions	Length	12.14 mm [.478 in]
	Height	3.5 mm [.138 in]
Usage Conditions	Operating Temperature Range (°C)	-30 – 85
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Tape & Reel
	Packaging Quantity	750

