




HALF-SIZE RELAYS



Active

TE CONNECTIVITY (TE)
HFW1201F01 = M39016/6-123L
CII

HFW1201F01
TE Internal Number: 2-1617030-0
Mil-Spec: M39016/6-123L

Not EU RoHS or ELV Compliant
[Find Compliant Alternatives](#)

Contact Arrangement **2 Form C, DPDT, 2 C/O**

Input Voltage (VDC) **6**

Contact Current Rating (A) **2**

Coil Voltage Rating (VDC) **6**

Coil Resistance (Ω) **40**

Catalog Pages/Data Sheets

RELAY
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features	Coil Latching	Without
	Product Type	Relay
	MOSFET Driver	Without
	Relay Type	Military/Aerospace High Performance
	Enclosure Type	Hermetically Sealed
Configuration Features	Transistor Driver	Without
Electrical Characteristics	Input Voltage (VDC)	6
	Coil Voltage Rating (VDC)	6
	Coil Resistance (Ω)	40
	Coil Power Rating (DC) (mW)	900
	Coil Suppression Diode	Without
	Actuating System	DC
	Vibration	30G's, 10 – 3000Hz
	Coil Magnetic System	Non-Polarized, Monostable
	Coil Power Measurement	Milliwatts
	Coil Polarity Protection Diode	Without
Contact Features	Shock	100G's, 6ms
	Contact Arrangement	2 Form C, DPDT, 2 C/O
	Contact Current Rating (A)	2

Termination Features	Termination Type	PC Pins
Mechanical Attachment	Mounting Type	Printed Circuit Board
Usage Conditions	Operating Temperature Range (°C)	-65 – 125
Product Compliance	<div>Statement of Compliance</div> <div>PDF</div> <div>VIEW ALL PRODUCT COMPLIANCE</div>	