



CIRCUIT PROTECTION

RADIAL-LEADED DEVICES



✓ Active

TE CONNECTIVITY (TE)

RKEF375

Raychem | PolySwitch Devices , PPTC , RKEF

RKEF375

TE Internal Number: RF3375-000

Always EU RoHS/ELV Compliant

Hold Current (Room Temperature) (A) **3.75**

Voltage (Max) (V) **60**

Current (Max) (A) **40**

Lead Type **Straight**

Trip Current (Room Temperature) (A) **7.5**

Catalog Pages/Data Sheets

CATALOG PAGES FOR POLYSWITCH RADIAL

PDF
English

Product Specifications

Product Specification

RKEF375

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Product Type

PolySwitch Resettable Devices

Electrical Characteristics

Hold Current (Room Temperature) (A)	3.75
Voltage (Max) (V)	60
Current (Max) (A)	40
Trip Current (Room Temperature) (A)	7.5
Resistance (Min) (Ω)	.017
Resistance (Max) (Ω)	.04
Resistance (Max) (20°C, 1-Hr Post Trip) (Ω)	.06
Time to Trip (Max) (seconds)	22
Power Dissipation (Typical) (W)	3.4



Body Features

Lead Type

Straight

Lead Spacing (mm)

10.15

Lead spacing (mm) **10.15**

Coating **Coated**

Termination Features Construction **Radial-Leaded**

Usage Conditions Operating Temperature (Max) (°C) **85**





Industry Standards
CSA File Number **CA78165**
TUV Certificate Number **Available on Request (per IEC 60730-1)**
UL File Number **E74889**

Packaging Features Packaging Method **Bag**

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

RADIAL-LEADED DEVICES	RECTANGULAR POWER CONNECTORS	RECTANGULAR POWER CONNECTORS	WIRE-TO-BOARD HEADERS & RECEPTACLES
			
RXEF375 RXEF375	06P MICRO MNL ASSY, VRT, THRU, LF 3-794681-6	02P MICRO MNL ASSY, VRT, THRU, LF 3-794682-2	14 MTE HDR SRST LATCH .100CL 6-103735-3
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products