



 CIRCUIT PROTECTION

## RADIAL-LEADED DEVICES



✓ Active

TE CONNECTIVITY (TE)

### RKEF250K

[Raychem](#) | [PolySwitch Devices](#) , [PPTC](#) , [RKEF](#)

RKEF250K

TE Internal Number: RF3373-000

[Always EU RoHS/ELV Compliant](#)

Hold Current (Room Temperature) (A) **2.5**

Voltage (Max) (V) **60**

Current (Max) (A) **40**

Lead Type **Straight**

Trip Current (Room Temperature) (A) **5**

### Catalog Pages/Data Sheets

#### CATALOG PAGES FOR POLYSWITCH RADIAL

PDF  
**English**

### Product Specifications

Product Specification

[RKEF260K](#)

PDF  
**English**



Please review product documents or [contact us](#) for the latest agency approval information.



Product Type Features

Product Type

**PolySwitch Resettable Devices**

Electrical Characteristics

Hold Current (Room Temperature) (A)

**2.5**

Voltage (Max) (V)

**60**

Current (Max) (A)

**40**

Trip Current (Room Temperature) (A)

**5**

Resistance (Min) ( $\Omega$ )

**.04**

Resistance (Max) ( $\Omega$ )

**.085**

Resistance (Max) (20°C, 1-Hr Post Trip) ( $\Omega$ )

**.14**

Time to Trip (Max) (seconds)

**15.6**

Power Dissipation (Typical) (W)

**2.8**

Body Features

Lead Type

**Straight**

Lead Spacing (mm)

**5.08**

	Lead spacing (mm)	<b>3.00</b>
	Coating	<b>Coated</b>
Termination Features	Construction	<b>Radial-Leaded</b>
Usage Conditions	Operating Temperature (Max) (°C)	<b>85</b>
Industry Standards	CSA File Number	<b>CA78165</b>
	TUV Certificate Number	<b>Available on Request (per IEC 60730-1)</b>
	UL File Number	<b>E74889</b>
Packaging Features	Packaging Method	<b>Bag</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	