

RADIAL-LEADED DEVICES



TE CONNECTIVITY (TE)
RHEF1400

Raychem | PolySwitch Devices , PPTC , RHEF

RHEF1400

TE Internal Number: RF3326-000

Always EU RoHS/ELV Compliant

Hold Current (Room Temperature) (A) 14

Voltage (Max) (V) 16

Current (Max) (A) 100

Lead Type Bottle Kink

Trip Current (Room Temperature) (A) 27

Catalog Pages/Data Sheets

CATALOG PAGES FOR POLYSWITCH RADIAL

PDF **English**

Product Specifications

Product Specification RHEF1400

PDF **English**



Product Type Features	Product Type	PolySwitch Resettable Devices
Electrical Characteristics	Hold Current (Room Temperature) (A)	14
	Voltage (Max) (V)	16
	Current (Max) (A)	100
	Trip Current (Room Temperature) (A)	27
	Resistance (Min) (Ω)	.003
	Resistance (Max) (Ω)	.006
	Resistance (Max) (20°C, 1-Hr Post Trip) (Ω)	.009
	Time to Trip (Max) (seconds)	13
	Power Dissipation (Typical) (W)	6.9

Body Features Lead Type Bottle Kink

Land Charing (mm)

10 15

Leau эрасіну (піпі)

10.15

Coating Coated

Termination Features	Construction	Radial-Leaded
Usage Conditions	Operating Temperature (Max) (°C)	125
Industry Standards	CSA File Number TUV Certificate Number UL File Number	CA78165 Available on Request (per IEC 60730-1) E74889
Packaging Features	Packaging Method	Bag
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE