

## **RADIAL-LEADED DEVICES**



TE CONNECTIVITY (TE)
RKEF050

Raychem | PolySwitch Devices , PPTC , RKEF

RKEF050

TE Internal Number: RF3054-000

Always EU RoHS/ELV Compliant

Hold Current (Room Temperature) (A) .5

Voltage (Max) (V) 60

Current (Max) (A) 40

Lead Type Standard Kink

Trip Current (Room Temperature) (A) 1

Catalog Pages/Data Sheets

CATALOG PAGES FOR POLYSWITCH RADIAL

PDF **English** 

**Product Specifications** 

Product Specification RKEF050

PDF **English** 

Please review product documents or contact us for the latest agency approval information.

	Product Type Features	Product Type	PolySwitch Resettable Devices
	Electrical Characteristics	Hold Current (Room Temperature) (A)	.5
y		Voltage (Max) (V)	60
în		Current (Max) (A)	40
_		Trip Current (Room Temperature) (A)	1
<b>G</b>		Resistance (Min) ( $\Omega$ )	.32
V		Resistance (Max) ( $\Omega$ )	.529
		Resistance (Max) (20°C, 1-Hr Post Trip) (Ω)	.9
		Time to Trip (Max) (seconds)	.8
		Power Dissipation (Typical) (W)	1

Body Features Lead Type Standard Kink

Lead spacing (IIIIII)

Coating

J.U0

Coated

Termination Features	Construction	Radial-Leaded
Usage Conditions	Operating Temperature (Max) (°C)	85
Industry Standards	CSA File Number  TUV Certificate Number  UL File Number	CA78165  Available on Request (per IEC 60730-1)  E74889
Packaging Features	Packaging Method	Bag
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

## **CUSTOMERS ALSO BOUGHT**

