



RELAYS, CONTACTORS & SWITCHES

TO-5/.100 GRID



✓ Active

↓ 3D PDF

TE CONNECTIVITY (TE)

JMSC-26XMS = M39016/11-044M

CII

JMSC-26XMS

TE Internal Number: 1617127-9

Mil-Spec: M39016/11-044M

[Not EU RoHS or ELV Compliant](#)

[Find Compliant Alternatives](#)

Contact Arrangement **2 Form C, DPDT, 2 C/O**

Input Voltage (VDC) **26.5**

Coil Suppression Diode **Without**

MOSFET Driver **Without**

Transistor Driver **Without**

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[5-1773450-5_sec1_MS](#)

PDF
English



Please review product documents or [contact us](#) for the latest agency approval information.



Product Type Features

MOSFET Driver

Without

Enclosure Type

Hermetically Sealed

Product Type

Relay

Relay Type

Military/Aerospace High Performance

Configuration Features

Transistor Driver

Without

Electrical Characteristics

Input Voltage (VDC)

26.5

Coil Suppression Diode

Without

Coil Suppression Diode	without
Coil Voltage (VDC)	26.5
Coil Resistance (Ω)	3300
Coil Power Rating (DC) (mW)	213
Coil Polarity Protection Diode	Without
Actuating System	DC
Vibration	30G's, 10 – 3000Hz
Coil Power Measurement	Milliwatts
Coil Magnetic System	Non-Polarized, Monostable
Shock	75G's, 6ms

Contact Features	Contact Arrangement	2 Form C, DPDT, 2 C/O
	Contact Current Rating (A)	1
	Pin Configuration	.2 x .3" Spreader Pad
	Contact Current Class	Low Level – 1 A

Termination Features	Termination Type	Long Leads
----------------------	------------------	-------------------

Mechanical Attachment	Mounting Type	Printed Circuit Board
-----------------------	---------------	------------------------------

Usage Conditions	Operating Temperature Range ($^{\circ}\text{C}$)	-65 – 125
------------------	--	------------------

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)