



TE Connectivity: Every Connection Counts
© 2017 TE Connectivity Ltd. family of companies. All Rights Reserved

Relays, Contactors & Switches > Relays > Mil-Aero Relays > TO-5/.100 Grid



TE CONNECTIVITY (TE)
JMAPD-26XM = M39016/15-039M
[CII](#) | [MAD TO-5 Relay](#)

JMAPD-26XM
TE Internal Number: 1617124-4
Mil-Spec: M39016/15-039M

[Not EU RoHS Compliant](#)
[Not EU ELV Compliant](#)

Contact Arrangement **2 Form C, DPDT, 2 C/O**

Input Voltage (VDC) **26.5**

Coil Suppression Diode **With**

MOSFET Driver **Without**

Transistor Driver **Without**

Active

3D PDF

CAD Files

- [3D PDF](#)
PDF
3D
- [Customer View Model](#)
2D_DXF.ZIP
English
- [Customer View Model](#)
3D_IGS.ZIP
English
- [Customer View Model](#)
3D_STP.ZIP
English

Catalog Pages/Data Sheets

RELAY

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features	MOSFET Driver	Without
	Product Type	Relay
	Relay Type	Military/Aerospace High Performance
	Enclosure Type	Hermetically Sealed
Configuration Features	Transistor Driver	Without
Electrical Characteristics	Coil Power Measurement	Milliwatts
	Input Voltage (VDC)	26.5
	Coil Suppression Diode	With
	Coil Voltage (VDC)	26.5
	Coil Resistance (Ω)	1560
	Coil Power Rating (DC) (mW)	450
	Coil Polarity Protection Diode	Without
	Shock	75G's, 6ms
	Actuating System	DC
	Vibration	30G's, 10 – 3000Hz



Coil Magnetic System

Non-Polarized, Monostable

Contact Features	Contact Arrangement	2 Form C, DPDT, 2 C/O
	Contact Current Rating (A)	1
	Contact Current Class	Low Level – 1 A
Termination Features	Termination Type	PC Pins
Mechanical Attachment	Mounting Type	Printed Circuit Board
Twitter LinkedIn Facebook Dropdown Usage Conditions	Operating Temperature Range (°C)	-65 – 125
	Statement of Compliance	
	PDF	




Compatible Products

> [Contact Product Support](#)

Also in the Series | [MAD TO-5 Relay](#)



Customers Also Bought

HEAT SHRINK BOOTS	RF CONNECTORS	SHIELDED CONTACTS	D-SUB CONNECTOR CONTACTS
 202D242-4/86-0 202D242-4/86-0	 2007 7141 02 1051137-1	 D-610-10 601064-000	 SZ 22 SOCKET CONTACT 204351-1

Twitter

LinkedIn

Facebook

▼