




Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **60**

Centerline (Pitch): **2 mm [.079 in]**

Features

Product Type Features

Series	Signal
PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Sequencing	No
Number of Rows	5
Stackable	No
Number of Signal Positions	60
PCB Mount Orientation	Vertical
Number of Positions	60
Board-to-Board Configuration	Vertical

Electrical Characteristics

Dielectric Withstanding Voltage (Max)	1000 VAC
Insulation Resistance	5 MΩ
Operating Voltage	30 VAC
Impedance	60 Ω

Contact Features

--



Contact Layout	Matrix
PCB Contact Termination Area Plating Material Thickness	3.81 μm[149.9997 μin]
Mating Post Length	6.5 mm[.256 in]
Contact Mating Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.05 μm[1.9685 μin]
Contact Type	Pin
Contact Current Rating (Max)	3 A

Termination Features

Termination Post & Tail Length	4.25 mm[.167 in]
Termination Method to Printed Circuit Board	Through Hole

Mechanical Attachment

PCB Mount Alignment Type	Locating Posts
Mating Alignment	With
Mating Alignment Type	Polarization
PCB Mount Retention	Without
PCB Mount Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	2 mm[.079 in]
Housing Color	Natural
Housing Material	LCP (Liquid Crystal Polymer)

Dimensions

Connector Width	18 mm[.709 in]
Connector Height	17 mm[.6681 in]
PCB Thickness (Recommended)	2.4 mm[.05 in]

Usage Conditions

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------



Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	24
Packaging Method	Tube

Other

Comment	Sequencing of the mating posts and lead lengths is available. Worksheets for this procedure may be found under Z-PACK 2mm FB General Information.
---------	---

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	ECHAによる現在の候補リスト: 2019年1月(197) 候補リストの表記: 2019年1月(197)
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Pin-in-Paste capable to 260°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.


Compatible Parts




TE Part # 223008-2
FB-5R,ASY,060,SIG,REC,
EN,3.55




TE Part # 223007-2
FB-5R,ASY,060,SIG,REC,SL,
3.53




TE Part # 5223008-2
FB-5R,ASY,060,SIG,REC,
EN,3.55



TE Part # 5223007-2
FB-5R,ASY,060,SIG,REC,SL,
3.53



TE Part # 223004-2
FB-5R,ASY,060,SIG,REC,SL,
2.73




TE Part # 5223004-2
FB-5R,ASY,060,SIG,REC,SL,
2.73

Also in the Series | Z-PACK Future Bus+



Board-to-Board Headers &
Receptacles(168)



Hard Metric Backplane
Connectors(1)



PCB Connector Shrouds(9)




Rectangular Power
Connectors(35)


Customers Also Bought




TE Part #2143330-1
1X6 QSFP Kit Assy Bhnd
Bzl,PCI




TE Part #104652-6
60 50/50 GRID DRST
SFMNT RCPT




TE Part #6469083-3
HMZD 3PAIR, HDR ASSY,
25MM MOD




TE Part #5745078-5
HD-20 RCPT 25P VERT
FFSCRLK



TE Part #724447-000
DK-621-0435-2S



TE Part #817479-000
202D163-25/225-0



TE Part #5223524-2
2MMFB,5R,ASY,060,SIG,
HDR,EN



TE Part #2-103167-2
50 MODII HDR DRRR
SHRD .100CL



TE Part #292323-4
RECEPTACLE ASSY RIGHT
ANGLE STACKED THRU



TE Part #5353184-8
.6FHP04H,100,S,GIG,08/Sn,
TR,NSYes

Documents

Product Drawings

FB-5R,ASY,060,SIG,HDR,SL,4.25

English

CAD Files

Customer View Model

ENG_CVM_5223000-2_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_5223000-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_5223000-2_C.3d_stp.zip

English

3D PDF

English

Product Specifications

Application Specification

English