MBXL VERT RCPT 16S+5P ACTIVE



MULTI-BEAM

TE Part # 6450151-1 TE Internal #: 6450151-1

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Product Type: Connector Assembly

Housing Type: Receptacle

Connector System: Board-to-Board

Number of Positions: 21

Centerline (Pitch): 2.54 mm, 6.35 mm [.1 in, .25 in]

Features

Product Type Features

Product Type	Connector Assembly
Housing Type	Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Contact Type	Socket

Configuration Features

Mating & Unmating Configuration	Sequencing
Number of Positions	21
PCB Mount Orientation	Vertical
Number of Power Positions	5
Number of Signal Positions	16
Number of Rows	4
Row-to-Row Spacing	2.54 mm[.1 in]
Board-to-Board Configuration	Vertical
Electrical Characteristics	

Contact Features

Operating Voltage

Power Contact Material	Tin	
------------------------	-----	--

60 VDC, 200 VDC



Termination Post & Tail Length Termination Method to Printed Circuit Board Through Hole - Solder Mechanical Attachment PCB Mount Retention PCB Mount Retention Type Boardlock Connector Mounting Type Boardlock Connector Mounting Type Boardlock Connector Mounting Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire		
Contact Termination Area Plating Material Contact Mating Area Plating Material Contact Mating Area Plating Thickness .76 µm;30 µin] Underplate Material Thickness 3.43 µm Termination Features Termination Post & Tail Length 3.43 mm[.135 in] Termination Method to Printed Circuit Board Mechanical Attachment PCB Mount Retention With PCB Mount Retention Type Boardlock Connector Mounting Type Board Mount Mating Retention Type Boardlock Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UI Plammability Rating UI 94V-0 Housing Color Housing Material High Temperature Thermoplastic Usage Conditions Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Contact Current Rating (Max)	42 A
Contact Mating Area Plating Material Contact Mating Area Plating Thickness .76 µm(30 µin) Underplate Material Thickness 3.43 µm Termination Features Termination Post & Tail Length .3.43 mm .135 in Termination Method to Printed Circuit Board Through Hole - Solder Mechanical Attachment PCB Mount Retention With PCB Mount Retention Type Boardlock Connector Mounting Type Boardlock Housing Retention Type Boardlock Centerline (Pitch) LI Flammability Rating UI 94V 0 Housing Color Housing Material Usage Conditions Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Contact Retention	Without
Contact Mating Area Plating Thickness 7.6 µm[30 µin] Underplate Material Thickness 3.43 µm Termination Features Termination Post & Tail Length 3.43 mm[.135 in] Termination Method to Printed Circuit Board Through Hole - Solder Mechanical Attachment PCB Mount Retention With PCB Mount Retention Type Boardlock Connector Mounting Type Board Mount Mating Retention Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UI Flammability Rating UI 94V 0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Contact Termination Area Plating Material	Tin
Underplate Material Thickness 3.43 µm Termination Features Termination Post & Tail Length 3.43 mm[.135 in] Termination Method to Printed Circuit Board Through Hole Solder Mechanical Attachment PCB Mount Retention With PCB Mount Retention Type Boardlock Connector Mounting Type Board Mount Mating Retention Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part Not Glow Wire	Contact Mating Area Plating Material	Noble Metal
Termination Features Termination Post & Tail Length 3.43 mm .135 in Termination Method to Printed Circuit Board Through Hole - Solder Mechanical Attachment PCB Mount Retention Type Boardlock Connector Mounting Type Board Mount Mating Retention Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm .1 in .25 in UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Contact Mating Area Plating Thickness	.76 μm[30 μin]
Termination Post & Tail Length Termination Method to Printed Circuit Board Through Hole - Solder Mechanical Attachment PCB Mount Retention PCB Mount Retention Type Boardlock Connector Mounting Type Boardlock Connector Mounting Type Boardlock Connector Mounting Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Underplate Material Thickness	3.43 µm
Termination Method to Printed Circuit Board Mechanical Attachment PCB Mount Retention PCB Mount Retention Type Boardlock Connector Mounting Type Board Mount Mating Retention Type Boardlock Contector Mounting Type Board Mount Mating Retention Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V 0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Termination Features	
PCB Mount Retention With PCB Mount Retention Type Boardlock Connector Mounting Type Boardlock Mating Retention Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V-0 Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Termination Post & Tail Length	3.43 mm[.135 in]
PCB Mount Retention Type Boardlock Connector Mounting Type Board Mount Mating Retention Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Circuit Application Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Termination Method to Printed Circuit Board	Through Hole - Solder
PCB Mount Retention Type Board Mount Mating Retention Type Board Mount Mating Retention Type Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Mechanical Attachment	
Connector Mounting Type Mating Retention Type Board Mount Boardlock Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	PCB Mount Retention	With
Mating Retention Type Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	PCB Mount Retention Type	Boardlock
Housing Features Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Connector Mounting Type	Board Mount
Centerline (Pitch) 2.54 mm, 6.35 mm[.1 in][.25 in] UL P4V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Mating Retention Type	Boardlock
UL Flammability Rating UL 94V-0 Housing Color Black Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Housing Features	
Housing Color Housing Material High Temperature Thermoplastic Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Centerline (Pitch)	2.54 mm, 6.35 mm[.1 in][.25 in]
Housing Material Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Thermoplastic High Temperature Thermoplastic High Temperature Thermoplastic High Temperature Thermoplastic High Temperature Part - Not Glow Wire	UL Flammability Rating	UL 94V-0
Usage Conditions Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Housing Color	Black
Operating Temperature Range -20 – 105 °C[-4 – 221 °F] Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Housing Material	High Temperature Thermoplastic
Operation/Application Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Usage Conditions	
Circuit Application Power & Signal Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Operating Temperature Range	-20 - 105 °C[-4 - 221 °F]
Industry Standards Glow Wire Rating High Temperature Part - Not Glow Wire	Operation/Application	
Glow Wire Rating High Temperature Part - Not Glow Wire	Circuit Application	Power & Signal
	Industry Standards	
Packaging Features	Glow Wire Rating	High Temperature Part - Not Glow Wire
	Packaging Features	

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant

Box

TE Part # 6450151-1 TE Internal #: 6450151-1



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2019 (197) Candidate List Declared Against: JAN 2018 (181)
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.


Compatible Parts



Customers Also Bought











TE Part # 6450151-1 TE Internal #: 6450151-1






TE Part #1-5767005-2 MICT,495PLUG,190,ASSY,. 025,REC



TE Part #1-767005-1 MICT,495PLUG,152,ASSY,. 025,REC



TE Part #1-767007-4 MICT,260PLUG,266,ASSY,. 025,REC



RT PD E



TE Part #5821950-7
72 ME .050 LOW PROFILE
AU PB-FREE



Documents

Product Drawings

MBXL VERT RCPT 16S+5P

English

CAD Files

Customer View Model

ENG_CVM_CVM_6450151-1_C.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6450151-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6450151-1_C.3d_stp.zip

English

Datasheets & Catalog Pages

2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English

MBXL VERT RCPT 16S+5P

TE Part # 6450151-1 TE Internal #: 6450151-1

