

RAST

TE Internal #: 284865-5

Standard Edge Connectors, Wire-to-Board, 5 Positions, 2.5mm [. 098in] Centerline, Insulation Displacement Crimp (IDC), 1 Rows,

Natural Housing Color

View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > Standard Edge Connectors











Connector System: Wire-to-Board

Number of Positions: 5

Centerline (Pitch): 2.5 mm [.098 in]

Termination Method to Wire & Cable: Insulation Displacement Crimp (IDC)

Number of Rows: 1

Features

Product Type Features

Connector System	Wire-to-Board
Connector & Housing Type	Plug
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Card Entry Style	Side
Compatible With Wire & Cable Type	Discrete Wire
Number of Positions	5
Number of Rows	1
Connector Contact Load Condition	Fully Loaded

Electrical Characteristics

Operating Voltage	63 VAC	

Body Features

Keying Between Cavity Locations	2&3
Connector Profile	Standard



Contact Features

Contact Retention Within Housing	Without
PCB Contact Termination Area Plating Material Thickness	$4-10~\mu m$
Contact Type	Socket
Contact Mating Area Plating Material	Pre-Tin
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	2 A

Termination Features

Termination Method to Wire & Cable Insulation Displacement Crimp (IDC)	
--	--

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	With
Panel Mount Feature	Without
PCB Mount Retention	With

Housing Features

Housing Entry Configuration	Both Ends Closed
Centerline (Pitch)	2.5 mm[.098 in]
Housing Color	Natural
Housing Material	PBT GF

Dimensions

Card Slot Depth	5 mm
Connector Height	7.35 mm
PCB Thickness (Recommended)	1.5 mm[.059 in]
Accepts Wire Insulation Diameter Range	1.3 – 2.1 mm[.05 – .08 in]
Wire Size	.22 – .35 mm²

Usage Conditions

Operating Temperature Range -40 – 110 °C[-40 – 230 °F]	Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
--	-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal	
	3.9.1	



Packaging Features

Packaging Method	Tray
Packaging Quantity	308

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JAN 2020 (205) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought






TE Model / Part #293039-2 7 POS. F.F. TAB HSG MOTOR MOUNT WATER-PR



TE Model / Part #2-284865-6 DUOPLUG SL, FEMALE CONN., 6 POS, FULLY L



TE Model / Part #284865-4 Direct mount card edge conn.,




TE Model / Part #1-1740533-6

AMP DUOPLUG POW CONNECTOR




TE Model / Part #1-284745-1 AMP MONO-SHAPE 6POS TAB CONN O



TE Model / Part #293044-1 7 POS. FASTIN-FASTON* TAB HOUSING, RAST5



TE Model / Part #1-282042-3 AMP MONO-SHAPE P.C.B.CONN2P. GL



TE Model / Part #293015-1 7 POS. FASTIN FASTON TAB HSG.



TE Model / Part #1-282042-6 AMP MONO-SHAPE P.C.B.CONN



POSITION ASSY

Documents

Product Drawings

Direct mount card edge conn.,

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_284865-5_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_284865-5_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_284865-5_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages



1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_284865-5_062520181347_dmtec

English

MD_284865-5_062520181347_dmtec

English

Agency Approvals

Agency Approval Document

English