



Sensors > Flow Sensors > Flow Switch > 3/8 BSP MALE WATER FLOW SWITCH



Port Fitting: 3/8" BSP

Case Material: Noryl

Flow Switch on Rate: .6

Switching Current (Max): 1 A

Operating Temperature Range: -30 – 85 °C [ -22 – 185 °F ]

[All 3/8 BSP MALE WATER FLOW SWITCH \(2\)](#)

Features

Electrical Characteristics

|                         |     |
|-------------------------|-----|
| Switching Current (Max) | 1 A |
|-------------------------|-----|

Body Features

|               |       |
|---------------|-------|
| Case Material | Noryl |
|---------------|-------|

Usage Conditions

|                             |                           |
|-----------------------------|---------------------------|
| Operating Temperature Range | -30 – 85 °C[-22 – 185 °F] |
|-----------------------------|---------------------------|

Other

|                     |          |
|---------------------|----------|
| Port Fitting        | 3/8" BSP |
| Flow Switch on Rate | .6       |

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

|                                               |                                              |
|-----------------------------------------------|----------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                    |
| EU ELV Directive 2000/53/EC                   | Compliant                                    |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold      |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241) |



Candidate List Declared Against: JUNE 2023 (235)

SVHC > Threshold:

PDPP (45% in component)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

|                           |                                            |
|---------------------------|--------------------------------------------|
| Halogen Content           | Not Yet Reviewed for halogen content       |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Also in the Series | MEAS FCS



Flow Switch(6)

Customers Also Bought



TE Part #M3031-000005-100PG  
PRESS XDCR M3031-000005-100PG

Documents

Product Drawings  
FCS-01 FLOW SWITCH



English

Datasheets & Catalog Pages

FCS-01

English