BAT-HLD-012-THM ACTIVE

TE Internal #: BAT-HLD-012-THM
Battery Holders, CR1216 / CR1225, 1 Position, Horizontal, Nickel,
PCB Mount Alignment, Power, -22 – 158 °F [-30 – 70 °C]

View on TE.com >



Connectors > PCB Connectors > Battery Connectors & Holders > Battery Holders



Battery Compatibility: CR1216, CR1225

Number of Positions: 1

PCB Mount Orientation: Horizontal

Contact Mating Area Plating Material: Nickel

PCB Mount Alignment: With

Features

Product Type Features

Connector System	Board-to-Component
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	1
PCB Mount Orientation	Horizontal
Body Features	
Battery Holder Material	Phosphor Bronze
Battery Holder Type	Coin Cell

Contact Features

Battery Weight

Primary Product Color

Battery Compatibility

Contact Mating Area Plating Material	Nickel	
Some of Manning / Working Material	, troitor	

.7 g

Silver

CR1216, CR1225

Mechanical Attachment

PCB Mount Alignment Type	Retention Solder Tails
Connector Mounting Type	Board Mount
PCB Mount Alignment	With

Usage Conditions



Operating Temperature Range	-30 – 70 °C[-22 – 158 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Quantity	500
Packaging Method	Bulk

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





Customers Also Bought



TE Part #776164-2 35POS,AMPSEAL,SOC HSG ASSY,SLD, COD 2



TE Part #323915
TERMINAL,PIDG R 26-22 6



TE Part #640454-6 06P MTA100 HDR ASSY SQ STR POL



TE Part #5-102618-1 06 MODII HDR DRST SHRD .100CL













Documents

Product Drawings

Battery Holder 1216 1225 THM Bulk Pack

English

CAD Files

Customer View Model

ENG_CVM_CVM_BAT-HLD-012-THM_B.2d_dxf.zip

English

Customer View Model

Battery Holders, CR1216 / CR1225, 1 Position, Horizontal, Nickel, PCB Mount Alignment, Power, -22 – 158 °F [-30 – 70 °C]



ENG_CVM_CVM_BAT-HLD-012-THM_B.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_BAT-HLD-012-THM_B.3d_igs.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

CR1216, 1225 HOLDER OUTLINE THROUGH HOLE MOUNT

English