





Two-Piece Terminal Block Connectors

**Plug,
Right-Angle,
2.5 mm² Solid Wire,
5.0 mm Centerline,
UL Rating – 300 V, 12 A
12-30 AWG**







Suggested Screw Torque—
7 in.-lb.

No. of Positions	Dim. A	Part Numbers			
		Gray	Green	Blue	Black
2	10.0 [0.394]	282804-2	796640-2	796696-2	796641-2
3	15.0 [0.591]	282804-3	796640-3	796696-3	796641-3
4	20.0 [0.787]	282804-4	796640-4	796696-4	796641-4
5	25.0 [0.984]	282804-5	796640-5	796696-5	796641-5
6	30.0 [1.181]	282804-6	796640-6	796696-6	796641-6
7	35.0 [1.378]	282804-7	796640-7	796696-7	796641-7
8	40.0 [1.575]	282804-8	796640-8	796696-8	796641-8
9	45.0 [1.772]	282804-9	796640-9	796696-9	796641-9
10	50.0 [1.968]	1-282804-0	1-796640-0	1-796696-0	1-796641-0
11	55.0 [2.165]	1-282804-1	1-796640-1	1-796696-1	1-796641-1
12	60.0 [2.362]	1-282804-2	1-796640-2	1-796696-2	1-796641-2
13	65.0 [2.559]	1-282804-3	1-796640-3	1-796696-3	1-796641-3

Note: BUCHANAN Terminal Block Series B52C4UxxT has been replaced with 796696-xx (blue) and 796641-xx (black).
RDI Terminal Block Series 5ESDV-XX has been replaced with 796640-xx (green) or 796641-xx (black).

No. of Positions	Dim. A	Part Numbers			
		Gray	Green	Blue	Black
14	70.0 [2.756]	1-282804-4	1-796640-4	1-796696-4	1-796641-4
15	75.0 [2.953]	1-282804-5	1-796640-5	1-796696-5	1-796641-5
16	80.0 [3.150]	1-282804-6	1-796640-6	1-796696-6	1-796641-6
17	85.0 [3.346]	1-282804-7	1-796640-7	1-796696-7	1-796641-7
18	90.0 [3.543]	1-282804-8	1-796640-8	1-796696-8	1-796641-8
19	95.0 [3.740]	1-282804-9	1-796640-9	1-796696-9	1-796641-9
20	100.0 [3.937]	2-282804-0	2-796640-0	2-796696-0	2-796641-0
21	105.0 [4.134]	2-282804-1	2-796640-1	2-796696-1	2-796641-1
22	110.0 [4.331]	2-282804-2	2-796640-2	2-796696-2	2-796641-2
23	115.0 [4.528]	2-282804-3	2-796640-3	2-796696-3	2-796641-3
24	120.0 [4.724]	2-282804-4	2-796640-4	2-796696-4	2-796641-4
25	125.0 [4.921]	2-282804-5	2-796640-5	2-796696-5	2-796641-5

**Plug,
Right-Angle
2.5 mm² Solid Wire,
5.08 mm Centerline,
UL Rating – 300 V, 12 A
12-30 AWG**



Suggested Screw Torque—
7 in.-lb.

No. of Positions	Dim. A	Part Numbers		
		Gray	Green	Black
2	10.16 [0.400]	282806-2	796634-2	796635-2
3	15.24 [0.600]	282806-3	796634-3	796635-3
4	20.32 [0.800]	282806-4	796634-4	796635-4
5	25.40 [1.000]	282806-5	796634-5	796635-5
6	30.48 [1.200]	282806-6	796634-6	796635-6
7	35.56 [1.400]	282806-7	796634-7	796635-7
8	40.64 [1.600]	282806-8	796634-8	796635-8
9	45.72 [1.800]	282806-9	796634-9	796635-9
10	50.80 [2.000]	1-282806-0	1-796634-0	1-796635-0
11	55.88 [2.200]	1-282806-1	1-796634-1	1-796635-1
12	60.96 [2.400]	1-282806-2	1-796634-2	1-796635-2
13	66.04 [2.600]	1-282806-3	1-796634-3	1-796635-3

Note: RDI Terminal Block Series 2ESDV-xx has been replaced with 796634-xx (green) and 796635-xx (black).

No. of Positions	Dim. A	Part Numbers		
		Gray	Green	Black
14	71.12 [2.800]	1-282806-4	1-796634-4	1-796635-4
15	76.20 [3.000]	1-282806-5	1-796634-5	1-796635-5
16	81.28 [3.200]	1-282806-6	1-796634-6	1-796635-6
17	86.36 [3.400]	1-282806-7	1-796634-7	1-796635-7
18	91.44 [3.600]	1-282806-8	1-796634-8	1-796635-8
19	96.52 [3.800]	1-282806-9	1-796634-9	1-796635-9
20	101.60 [4.000]	2-282806-0	2-796634-0	2-796635-0
21	106.68 [4.200]	2-282806-1	2-796634-1	2-796635-1
22	111.76 [4.400]	2-282806-2	2-796634-2	2-796635-2
23	116.84 [4.600]	2-282806-3	2-796634-3	2-796635-3
24	121.92 [4.800]	2-282806-4	2-796634-4	2-796635-4
25	127.00 [5.000]	2-282806-5	2-796634-5	2-796635-5