

Home > Products > Relays > Product Feature Selector > Product Details

9-1415542-8 Product Details

 Share

 Print

 Email



9-1415542-8

TE Internal Number: 9-1415542-8
 Active

Industrial Relays (General Purpose)

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- PT Series
- Contact - Current Class = 5A to 10A Class, Less Than 16A
- Contact - Rated Current = 6 A
- Terminal Type = PCB-THT
- Contact - Arrangement = 4 Form C (CO)

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Electrical Characteristics:

- Contact - Current Class = 5A to 10A Class, Less Than 16A
- [Contact - Rated Current \(A\)](#) = 6
- Contact - Limiting Continuous Current (A) = 6
- Contact - Limiting Making Current (A) = 12
- Contact - Limiting Breaking Current (A) = 6
- Insulation - Initial Dielectric Between Coil/Contact Class = 1500V to 2500VA Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 1200
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 2500
- Contact - Rated Voltage (VAC) = 240
- Contact - Switching Voltage Max. (VAC) = 240
- Contact - Limiting Short-Time Current (A) = 300
- Contact - Switching Recommended Load, Min. = 1mA at 0.02V
- Coil - Rated Voltage (VDC) = 220
- [Coil - Resistance \(Ω\)](#) = 64533
- [Coil - Rated Power, DC \(mW\)](#) = 750
- Coil - Rated Power Class = 600mW to 800mW Class
- Insulation - Initial Dielectric Between Adjacent Contacts (V rms) = 2000
- Insulation - Creepage Class = 3mm to 5.5mm Class
- Insulation - Clearance Class = 2.5mm to 4mm Class
- Insulation - Special Features = 5000V Initial Surge Withstand Voltage between Contacts and Coil

Dimensions:

- Mechanical - Length Class = 25mm to 30mm Class
- Length (mm [in]) = 28.00 [1.102]
- Mechanical - Width Class = 20mm to 25mm Class
- Width (mm [in]) = 22.50 [0.886]
- Mechanical - Height Class = 25mm to 30mm Class
- Height (mm [in]) = 29.00 [1.142]
- Insulation - Clearance Between Contact and Coil (mm [in]) = 4 [0.157]
- Insulation - Creepage Between Contact and Coil (mm [in]) = 4 [0.157]

Body Features:

- Weight (g [oz]) = 30.00 [1.058]

Contact Features:

- Terminal Type = PCB-THT
- Contact Material = AgNi90/10, gold plated
- Contact - Number of Poles = 4

Configuration Features:

- [Contact - Arrangement](#) = 4 Form C (CO)
- [Coil - Magnetic System](#) = Monostable, DC

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- Approved/Registered Standards = cULus, LLOYDs, VDE

Environmental:

- Environmental - Category of Protection = RTII
- Environmental - Ambient Temperature, Max. (°C [°F]) = 70 [158]
- Environmental - Ambient Temperature Class = 50°C to 70°C Class

Packaging Features:

- Packaging Method = Tube

Other:

- [Series](#) = PT
- Brand = Schrack
- Additional Features = Manual Operation, Mechanical Indicator

Corporate Information

[About TE](#)

[Investors](#)

Quick Links

[Distributor Inventory](#)

[Product Cross Reference](#)

Customer Support

[Email or Chat With Us](#)

[Find a Phone Number](#)

Keep Me Informed



[News Room](#)

[Supplier Portal](#)

[Careers](#)

[Terms & Conditions](#)

[Privacy Policy](#)

[AODA Accessibility Policy](#)

[AODA Multi-Year Accessibility
Plan](#)

[Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

[Knowledge Base](#)

[Manage Your Account](#)

