




# 1-282925-2 Product Details

[Share](#) | [Print](#) | [Email](#)


**1-282925-2**

TE Internal Number: 1-282925-2

Active

## Terminal Block Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

### Product Highlights:

- Connector
- Type of Connector = Wire Receptacle
- Housing Color = Green
- Not Side Stackable
- Without Screw Flange

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

## Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- [Product Type](#) = Connector
- [Type of Connector](#) = Wire Receptacle
- [Mount Angle](#) = Vertical
- [Screw Size](#) = M3

### Electrical Characteristics:

- [Amperes \(A\)](#) = 24.0
- [Voltage \(VAC\)](#) = 300

### Dimensions:

- [PCB Tail Length \(mm \[in\]\)](#) = 4.00 [0.157]

### Body Features:

- [Wire Entry Angle](#) = Side
- [Closed End](#) = Without
- [Stacked Levels](#) = Level 3
- [Interlock](#) = With
- [Wire Range \(mm \[AWG\]\)](#) = 0.05-3.00<sup>2</sup> [30-12]
- [Screw Material](#) = Brass
- [Screw Plating](#) = Nickel

### Contact Features:

- [Contact Base Material](#) = Brass
- [Contact Plating, Mating Area, Material](#) = Tin

### Housing Features:

- [Housing Color](#) = Green
- [Centerline \(mm \[in\]\)](#) = 5.08 [0.200]
- [Housing Material](#) = Polyamide 6.6 GF

### Configuration Features:

- [Side Stackable](#) = No
- [Screw Flange](#) = Without
- [Number of Positions](#) = 2

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C
- [RoHS/ELV Compliance History](#) = Always was RoHS compliant
- [UL Flammability Rating](#) = UL 94V-0

### Packaging Features:

- [Packaging Quantity](#) = 200

### Other:

- [Brand](#) = Buchanan
- [Comment](#) = 20A Field Wiring. Black Ink Marking. Sections glued using cyanolit 24IF or TE engineering approved equivalent.

Feedback

## Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

## Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

## Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

## Keep Me Informed



