RT214730 Product Details



RT214730
(1419108-6)
TE Internal Number: 1419108-6
Active

View 3D PDF

Industrial Relays (General Purpose)

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- RT1 Series
- Contact - Current Class = 10A to 20A Class, Less Than 16A
- Contact - Rated Current = 12 A
- Terminal Type = PCB-THT, Plug-in
- Contact - Arrangement = 1 Form C (CO)

View all Features

Add to My Part List | Request Sample | Find Similar Products | Buy Product

Quick Links

- Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- None Available

Catalog Pages/Data Sheets:
- Power PCB Relay RT1 (PDF, English)

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files: (CAD Format & Compression Information)
- 2D Drawing (DXF, Version D)
- 3D Model (IGES, Version D)
- 3D Model (STEP, Version D)

List all Documents

Additional Information:
- Product Line Information

Related Products:
- Tooling

Product Features (Please use the Product Drawing for all design activity)

Electrical Characteristics:
- Contact - Current Class = 10A to 20A Class, Less Than 16A
- Contact - Rated Current (A) = 12
- Contact - Limiting Continuous Current (A) = 12
- Contact - Limiting Making Current (A) = 25
- Contact - Limiting Breaking Current (A) = 12
- Insulation - Initial Dielectric Between Coil/Contact Class = >4000V Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 1000
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 5000
- Contact - Rated Voltage (VAC) = 250
- Contact - Switching Voltage Max. (VAC) = 400
- Contact - Limiting Short-Time Current (A) = 12
- Coil - Rated Voltage (VAC) = 230
- Coil - Resistance (Ω) = 32500
- Coil - Rated Power, AC (VA) = 1.00
- Coil - Rated Power Class = 0.5VAW to 1.0VA Class
- Insulation - Creepage Class = >8mm Class
- Insulation - Clearance Class = >8mm Class
- Insulation - Special Features = Tracking Index of Relay Base PTI250

Dimensions:
- Mechanical - Length Class = 25mm to 30mm Class
- Length (mm [in]) = 29.00 [1.142]
- Mechanical - Width Class = 12mm to 16mm Class
- Width (mm [in]) = 12.70 [0.500]
- Mechanical - Height Class = 15mm to 16mm Class
- Height (mm [in]) = 15.70 [0.618]

Body Features:
- Mount Type = PCB, Socket
- Weight (g [oz]) = 14.00 [0.494]

Contact Features:
- Terminal Type = PCB-THT, Plug-in
- Contact Material = AgNi90/10
- Contact - Number of Poles = 1

Configuration Features:
- Contact - Arrangement = 1 Form C (CO)
- Coil - Magnetic System = Monostable, AC
- Coil - Special Features = UL Coil Insulation Class F

Industry Standards:
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive
- Approved/Registered Standards = cCSAus, cULus, VDE

Environmental:
- Environmental - Category of Protection = RTII
- Environmental - Ambient Temperature, Max. (°C [°F]) = 70 [158]
- Environmental - Ambient Temperature Class = 50°C to 70°C Class

Packaging Features:
- Packaging Method = Tube

Feedback

- Insulation - Clearance Between Contact and Coil (mm [in]) = 10 [0.394]
- Insulation - Creepage Between Contact and Coil (mm [in]) = 10 [0.394]

Other:

- Series = RT1
- Brand = Schrack
- Accessories/Socket Type = DIN-rail Socket, PCB Socket



© 2014 TE Connectivity Ltd. family of companies. All Rights Reserved