

[My Cart](#)[My Part Lists](#)[Sign In/Register](#)[English \(Change\)](#)**Have a Question?**Chat with a Product
Information Specialist

What can we help you find?

[Products](#)[Industries](#)[Resources](#)[About TE](#)[My Account](#)[Innovation](#)[Support Center](#)

1825097-1 Product Details

[Share](#)[Print](#)[Email](#)

1825097-1
(TPB11CGPC004)
TE Internal Number: 1825097-1
 Active

Pushbutton Switches

[Always EU RoHS/ELV Compliant](#) (Statement of Compliance)

Product Highlights:

- Switch
- Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 0.4VA
- Operating Function = Off [On]

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)[Request Sample](#)[Find Similar Products](#)[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [PUSHBUTTON SWITCH, TPB SERIES](#) (PDF, English)

Catalog Pages/Data Sheets:

- [SWITCHES_CORE_PROGRAM_CATALOG](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

[List all Documents](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- Product Type = Switch
- Tactile = Yes
- [Series](#) = TPB
- Mount Angle = Vertical
- Termination Type = Printed Circuit
- Actuator Style = Round

Electrical Characteristics:

- Contact Rating = 0.4VA

Dimensions:

- Actuator Length (mm [in]) = 3.28 [0.129]

Body Features:

- Mount Style = Through-Hole
- Actuator Profile = Extended
- Actuator Color = Black
- Case Material = Thermoplastic (LCP)
- Actuator Material = Nylon

Contact Features:

- Contact Plating = Gold
- Contact Base Material = Copper Alloy

Housing Features:

- Process Sealed = No
- Low Profile = No

Configuration Features:

- Configuration (Pole-Throw) = Single Pole - Single Throw
- Operating Function = Off [On]
- Ganged = No
- ESD Grounding Terminal = Without
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Temperature Rating = Standard

Operation/Application:

- Actuator Force (g [oz]) = 50.00 – 400.00 [1.770 – 14.120]

Packaging Features:

- Packaging Method = Loose Piece

Other:

- Brand = Alcoswitch

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed

