




JLS91439FK Product Details



JLS91439FK
(1437566-7)

TE Internal Number: 1437566-7



Pushbutton Switches



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Switch
- Not Tactile
- Single Pole - Single Throw Configuration (Pole-Throw)
- Contact Rating = 1A
- Operating Function = Normally Closed, Momentary

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)



[Add to My Part List](#)



[Request Sample](#)



[Find Similar Products](#)



[Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [PUSH SWITCH, JLS SERIES](#) (PDF, English)

Catalog Pages/Data Sheets:

- [SWITCHES_CORE_PROGRAM_CATALOG](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Switch
- Mount Angle = Right Angle
- Actuator Style = Round

Electrical Characteristics:

- Contact Rating = 1A

Termination Features:

- Termination Type = Printed Circuit

Dimensions:

- Actuator Length (mm [in]) = 7.30 [0.287]
- Cap Diameter (mm [in]) = 6.40 [0.252]
- Cap Height (mm [in]) = 7.30 [0.287]

Body Features:

- Mount Style = Through-Hole
- Actuator Profile = Extended
- Actuator Color = Grey
- Bushing Style = Unthreaded
- Cap Color = Gray
- Case Material = Steel
- Actuator Material = Acetal

Contact Features:

- Contact Plating = Silver Clad Copper
- Contact Base Material = Copper Alloy

Housing Features:

- Process Sealed = No
- Low Profile = No

Configuration Features:

- Tactile = No
- Configuration (Pole-Throw) = Single Pole - Single Throw
- Operating Function = Normally Closed, Momentary
- Ganged = No
- ESD Grounding Terminal = Without
- Number of Actuators = Single
- Illuminated = No
- Dust Proof = No
- Support Bracket = Without
- Snap Action = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Operation/Application:

- Actuator Force (g [oz]) = 300.00 [10.582]

Packaging Features:

- Packaging Method = Loose Piece

Other:

- Series = JLS
- Brand = Alcoswitch

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[AODA Accessibility Policy](#)
[AODA Multi-Year Accessibility Plan](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed

