


K10P-11DT5-48 Product Details



K10P-11DT5-48



Power Plug-in Relays



[Converted to EU RoHS but not ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- K10 Series
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 15 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

[View all Features](#) | [Find Similar Products](#)

[Previous](#) [1](#) [2](#) [3](#) [4](#) [5](#) ... [20](#) [Next](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [K10 15 Amp General Purpose Miniature Relay](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [PCB Layout](#)
- [Wiring Diagram](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Termination Type](#) = .187 x .020 Quick Connect Terminals

Electrical Characteristics:

- [Contact Current Rating \(Amps.\)](#) = 15
- [Coil Resistance \(?\)](#) = 2600
- [Actuating System](#) = DC
- [Coil Power, Nominal \(W\)](#) = 0.90
- [Input Voltage \(VDC\)](#) = 48

Body Related Features:

- [Series](#) = K10
- Polarized = No

Contact Related Features:

- [Mounting Options](#) = Bracket Mount Case
- [Enclosure](#) = Enclosed
- FCC Part 68 Isolation = No
- Relay Type = General
- [Contact Material](#) = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm[in]) = 28.20 x 21.80 x 34.90 [1.111 x .858 x 1.375]
- Wiring Diagram = 2 Form C
- Approved Standards = UL Recognized, CSA Certified

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- [Coil Magnetic System](#) = Monostable
- [Coil Suppression Diode](#) = Without
- [Coil Selection Criteria](#) = Nominal Voltage
- Coil Latching = Without
- [LED Indicator](#) = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives
- Coil Insulation Classification = Class B

Other:

- Brand = Potter & Brumfield

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

2008 Tyco Electronics Corporation All Rights Reserved