



OCAB-D4-15-B3-01 Product Details

[Share](#) [Print](#) [Email](#)



OCAB-D4-15-B3-01

TE Internal Number: E80815-000

Active

Build Out Attenuators

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Fiber Optic Connector Type = D4
- Minimum Return Loss = ≥ 45 dB (PC) dB
- Nominal Attenuation = 15 - 15 dB
- Operating Wavelength = 1260 - 1360 nm
- Fiber Type = ITU-T: G.652 Micron

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:	<ul style="list-style-type: none">• None Available
Catalog Pages/Data Sheets:	<ul style="list-style-type: none">• None Available
Product Specifications:	<ul style="list-style-type: none">• None Available
Application Specifications:	<ul style="list-style-type: none">• None Available
Instruction Sheets:	<ul style="list-style-type: none">• None Available
CAD Files:	<ul style="list-style-type: none">• None Available

Related Products:	<ul style="list-style-type: none">• Tooling
--------------------------	---

Feedback

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:	<ul style="list-style-type: none">• Fiber Optic Connector Type = D4
Electrical Characteristics:	<ul style="list-style-type: none">• Minimum Return Loss (dB) = ≥ 45 dB (PC)• Nominal Attenuation (dB) = 15 - 15• Operating Wavelength (nm) = 1260 - 1360• Maximum Optical Power (mW) = 250
Termination Features:	<ul style="list-style-type: none">• Fiber Type (Micron) = ITU-T: G.652

Industry Standards:	<ul style="list-style-type: none">• RoHS/ELV Compliance = RoHS compliant, ELV compliant• Lead Free Solder Processes = Not relevant for lead free process• RoHS/ELV Compliance History = Always was RoHS compliant
Environmental:	<ul style="list-style-type: none">• Operating Temperature (°C) = -40 - +70• Storage Temperature (°C [°F]) = -40 - +85 [-40 - +185]
Other:	<ul style="list-style-type: none">• Brand = TE Connectivity

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



